



PLANS AND DOCUMENTS
referred to in the PDA
DEVELOPMENT APPROVAL



Approval no: DEV2013/430

Date: 4 AUGUST 2017

Caloundra South

Northern Locality – Precinct 2 & Part of Precinct 6

Plan of Development

9 June 2017

Contents

1	EXPLANATORY CONTENT	5
1.1	Plan of Development Purpose	5
1.2	Land to which this PoD Relates	5
1.3	Interpretation	5
1.4	Relationship to Other Legislation	6
1.5	Explanation of Plan of Development Structure and Assessment Process	6
1.5.1	Overall Operation of this PoD and Relationships to Other Approvals	7
1.5.2	Future Development Delivery Processes	8
2	APPROVED DEVELOPMENT (NO FURTHER ASSESSMENT)	12
2.1	Reconfiguring a Lot	12
2.2	Advertising Devices	13
2.3	Car Park (where associated with a Display Home and / or Sales Office)	13
2.4	Home Based Business	13
2.5	House or Display Home	13
2.6	Secondary Dwellings	14
2.7	Multiple Residential (duplex)	14
2.8	Park	15
2.9	Sales Office	15
2.10	Telecommunications Facility	15
2.11	Utility Installation	16
3	APPROVED DEVELOPMENT (COMPLIANCE ASSESSMENT)	17
3.1	Introduction	17
3.2	Sub-Precinct 2.1 – North Western Neighbourhood and Sub-Precinct 2.2 – Central Neighbourhood	17
3.2.1	Sub-Precinct Intent	17
3.2.2	Uses Subject to Compliance Assessment	18
3.2.3	Specific Design Criteria	19
3.2.4	Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precincts 2.1 and 2.2	20
3.3	Sub-Precinct 2.3 – South Western Neighbourhood, Sub-Precinct 2.4 – Southern Neighbourhood, Sub-Precinct 2.5 – South East Premium Neighbourhood and Sub-Precinct 2.6 – South Eastern Neighbourhood	26
3.3.1	Sub-Precinct Intent	26
3.3.2	Uses subject to Compliance Assessment	26
3.3.3	Specific Design Criteria	27
3.3.4	Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precincts 2.3, 2.4, 2.5 and 2.6	28
3.4	Sub-Precinct 2.7 – The Pocket	38

3.4.1	Sub-Precinct Intent	38
3.4.2	Uses Subject to Compliance Assessment	38
3.4.3	Specific Design Criteria	38
3.4.4	Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 2.7	39
3.5	Sub-Precinct 2.8 – District Centre	42
3.5.1	Sub-Precinct Intent	42
3.5.2	Uses Subject to Compliance Assessment	42
3.5.3	Specific Design Criteria	43
3.5.4	Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 2.8	48
3.6	Sub-Precinct 2.9 – Schools	50
3.6.1	Sub-Precinct Intent	50
3.6.2	Uses Subject to Compliance Assessment	51
3.6.3	Specific Design Criteria	52
3.6.4	Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 2.9	54
3.7	Sub-Precinct 6.1 – Eco Sanctuary	57
3.7.1	Sub-Precinct Intent	57
3.7.2	Uses Subject to Compliance Assessment	57
3.7.3	Specific Design Criteria	57
3.7.4	Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 6.1	60
3.8	Sub-Precinct 6.2 – Conservation	60
3.8.1	Sub-Precinct Intent	60
3.8.2	Uses Subject to Compliance Assessment	61
3.8.3	Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 6.2	61
3.9	Specific Use Criteria	62

Figures

Figure 1	Land to which this PoD relates
Figure 2	PoD Relationship and Operational overview
Figure 3	Approved Development (No Further Assessment) Operation
Figure 4	Approved Development (Compliance Assessment) Operation
Figure 5	Sub-Precincts
Figure 6	Sub Precincts 2.1 and 2.2 Fixed Elements
Figure 7	Sub-Precincts 2.3, 2.4, 2.5 and 2.6 Fixed Elements
Figure 8	Sub-Precinct 2.7 Fixed Elements
Figure 9	Sub-Precinct 2.8 Fixed Elements
Figure 10	Sub-Precinct 2.9 Fixed Elements

Tables

Table 1	Plan of Development Structure
Table 2	Approved Development (No Further Assessment) Process Summary
Table 3	Approved Development (Compliance Assessment) Process Summary
Table 4	Advertising Devices Controls
Table 5	House or Display Home Controls
Table 6	Sales Office Controls
Table 7	Telecommunications Facility Controls
Table 8	Utility Installation controls
Table 9	Uses for Sub-precincts 2.1 and 2.2
Table 10	Design Standards for Sub-precincts 2.1 and 2.2
Table 11	Design Standards for Lot Variations in Sub-precinct 2.1
Table 12	Design Standards for Lot Variations in Sub-precinct 2.2
Table 13	Uses for Sub-Precincts 2.3, 2.4, 2.5 and 2.6
Table 14	Design Standards for Sub-Precincts 2.3, 2.4, 2.5 and 2.6
Table 15	Design Standards for Lot Variations in Sub-precinct 2.3
Table 16	Design Standards for Lot Variations in Sub-precinct 2.4
Table 17	Design Standards for Lot Variations in Sub-precinct 2.5
Table 18	Design Standards for Lot Variations in Sub-precinct 2.6
Table 19	Uses for Sub-Precinct 2.7
Table 20	Design Standards for Sub-Precinct 2.7
Table 21	Design Standards for Lot Variations in for Sub-Precinct 2.7
Table 22	Uses for Sub-Precinct 2.8
Table 23	Design Standards for Sub-Precinct 2.8
Table 24	Design Standards for Lot Variations in Sub-Precinct 2.8
Table 25	Uses for Sub-Precinct 2.9
Table 26	Design Standards for Sub-Precinct 2.9
Table 27	Design Standards for Lot Variations in Sub-Precinct 2.9
Table 28	Uses for Sub-Precinct 6.1
Table 29	Design Standard for Sub-Precinct 6.1
Table 30	Uses for Sub-Precinct 6.2
Table 31	Specific Use Design Standards

Appendices

Appendix A	Definitions
Appendix B	Approved Reconfiguring a Lot Plan/s Ref 167100-112 Rev AC, 167100-114 Rev AC, 167100-116 Rev AC, 167100-118 Rev AC 167100-120 Rev AC, 167100-122 Rev AC, 167100-124 Rev AC, 167100-126 Rev AC, 167100-137 Rev AC and Development Statistics Plan Ref 167100-113 Rev AC
Appendix C	Overall Staging Plan Ref 167100-110 Rev AC
Appendix D	Signage Plan of Development Ref 167100-21-107_2Y
Appendix E	Approved Plans of Development Ref 167100-115 Rev AC, 167100-117 Rev AC, 167100-119 Rev AC, 167100-121 Rev AC, 167100-123 Rev AC, 167100-125 Rev AC , 167100-21-107_1Y (Plan of Development – Sub-Precincts), 167100-21-107_3Y(Small Non Residential Nodes and Business) and 167100-21-107_5Y(Connectivity)
Appendix F	Standard Allotment Diagrams Ref 167100-47X Sheet 1 of 15 to Sheet 15 of 15
Appendix G	Freestanding Telecommunications Facilities Plan Ref 167100-21-107_4Y and PMT (Transformer) Sites Ref 167100-21-107_7Y
Appendix H	Car Parking Rates
Appendix I	District Centre Plan of Development Ref 167100-21-50W, Mixed Use Site Plan of Development Ref 167100-21-132O and Temporary Sales & Display Villages Plan of Development Ref 167100-148H
Appendix J	School Plans of Development: State High School Site - Ref 167100-106P and Primary School Site - 167100-108U
Appendix K	Road Hierarchy Plan Ref 167100-21-107_6Y and Road Sections167100-30N Sheets 1 to 25
Appendix L	Eco-Centre Precinct Plan of Development Ref 167100-21-133M

I Explanatory Content

I.1 Plan of Development Purpose

- 1.1.1 This Plan of Development (PoD) has been prepared in accordance with the requirements of the approved Caloundra South Master Plan (Approved 15 June 2012) and will direct the development of land included within the Northern Locality – Precinct 2 & Part of Precinct 6 of the Master Plan.
- 1.1.2 This PoD refines the outcomes approved in the Master Plan.
- 1.1.3 This PoD describes the development that may occur within the Northern Locality – Precinct 2 & Part of Precinct 6 and the assessment criteria and / or approved plans that development must meet in any future assessment process.
- 1.1.4 The Caloundra South Urban Development Area Development Scheme (approved October 2011) sets the Vision for this community. The Caloundra South Master Plan identifies a range of principles, land use areas, localities and precinct entitlements and obligations. This PoD provides the instrument for the delivery of development that seeks to achieve the Vision and Principles outlined by these two documents.
- 1.1.5 If development is not in accordance with this PoD, it is to be assessed against the Caloundra South Urban Development Area Development Scheme (approved October 2011) and the Caloundra South Master Plan (15 June 2012).

I.2 Land to which this PoD Relates

- 1.2.1 This Plan of Development relates to that part of the Caloundra South Master Plan described as the Northern Locality – Precinct 2 & Part of Precinct 6 by the Caloundra South Master Plan (15 June 2012). **Figure 1 – Land to which this PoD relates** shows the boundary (defined by extent of the PoD area highlighted in red) of the land to which this PoD relates.




FIGURE 1 LAND TO WHICH THIS POD RELATES (EXTRACT FROM APPROVED CALOUNDRA SOUTH MASTER PLAN)

I.3 Interpretation

- 1.3.1 Terms used in this PoD have the meaning assigned to those terms by the Economic Development Act (ED) 2012, the Caloundra South Development Scheme 2011 and Part 13 of the Caloundra South Master Plan (as amended in red 15 June 2012). If there are any

inconsistencies between the definitions in these documents, the inconsistency is to be resolved by using the definition contained in the documents in the following order:-

- (a) the ED Act; or if there is no definition in the ED Act;
- (b) the Caloundra South UDA Development Scheme; or if there is no definition in the Caloundra South UDA Development Scheme,
- (c) Part 13 of the Caloundra South Master Plan (as amended in red 15 June 2012); or if there is no definition in Part 13 of the Caloundra South Master Plan (as amended in red 15 June 2012),
- (d) the definitions in **Appendix A** of this PoD.

1.3.2 A reference in the PoD to a specific resource document or standard means the current version of that resource document or standard.

1.3.3 A reference in the PoD to the Department of State Development Infrastructure and Planning (DSDIP) is taken to be a reference to a Nominated Assessing Authority pursuant to section 88 of the ED Act for a PDA development condition or approval.

1.4 Relationship to Other Legislation

1.4.1 The Council's Planning Scheme only applies to the extent it is adopted into the Development Scheme and Master Plan approval and then only to the extent the provisions so adopted are consistent with the PDA Development Scheme.

1.5 Explanation of Plan of Development Structure and Assessment Process

The PoD consists of the components outlined by **Table 1 – Plan of Development Structure** below.

TABLE 1 PLAN OF DEVELOPMENT STRUCTURE

SECTION		EXPLANATION
Providing non-statutory context and understanding of the PoD and how it is to be used	Section 1 Explanatory Content	This section includes general explanatory content regarding the site and how the PoD document is used, including:- - Relationship to all heads of power; - Structure of PoD; - How future assessment processes work; - The purpose of this document; - Land to which this PoD relates; - Rules for interpretation; and - The relationship of this PoD to other legislation.
Providing Development criteria and plans that form the statutory element of the PoD	Section 2 Approved Development (No Further Assessment)	This section outlines all development that is Approved Development (No Further Assessment) where in accordance with plans and criteria outlined in the PoD.
	Section 3 Approved Development (Compliance Assessment)	This section outlines all development that is Approved Development that can be considered through Compliance Assessment. This section is organised by sub-precinct and outlines the plans and criteria that are to be used in the compliance assessment process.

1.5.1 Overall Operation of this PoD and Relationships to Other Approvals

This PoD forms one element of the overall approval framework relevant to the Northern Locality – Precinct 2 & Part of Precinct 6.

The relationship of this PoD to other approvals or statutory obligations is outlined by **Figure 2 – PoD Relationship and Operational Overview**. This figure also provides a summary of the way in which future development can occur over the Northern Locality – Precinct 2 & Part of Precinct 6, which are:-

1. **Approved Development (No Further Assessment):** development in accordance with Plans and Development Controls comprising Exempt development, which may proceed to operational works and building works approvals; and
2. **Approved Development (Compliance Assessment):** development in accordance with the PoD subject to Compliance Assessment Process.

Further detail regarding each of these processes is outlined by **Section 1.5.2 Future Development Delivery Processes**.




FIGURE 2 POD RELATIONSHIP AND OPERATIONAL OVERVIEW

1.5.2 Future Development Delivery Processes

1.5.2.1 Approved Development (No Further Assessment)

Development within this section that is in accordance with the PoD is Exempt development and may proceed to operational works and building works approvals.

A summary of this process and its intended operation is provided by **Table 2 – Approved Development (No Further Assessment) Process Summary** and **Figure 3 – Approved Development (No Further Assessment) Operation**.

TABLE 2 APPROVED DEVELOPMENT (NO FURTHER ASSESSMENT) PROCESS SUMMARY

Section	What is the content?	When does this section apply?	How does it work?	Who administers the process?	Why is this process needed?
Section 2 For development in accordance with the PoD that is exempt from further assessment.	This section includes:- - Approved Plans for Reconfiguring a Lot; and - Approved Plans and development controls for approved uses.	Applies to development identified as Approved Development (No Further Assessment) for both Reconfiguring a Lot and Material Change of Use in Section 2 .	Approved Development (No Further Assessment) is development that is exempt from further assessment where in accordance with approved plans and development controls.	Development in accordance with these plans and controls will proceed to certification of operational works and building works.	This section identifies development that does not need to undertake a Compliance Assessment process.




FIGURE 3 APPROVED DEVELOPMENT (NO FURTHER ASSESSMENT) OPERATION

1.5.2.2 Approved Development (Compliance Assessment)

Approved Development (Compliance Assessment) means the process of having Development plans, works, documents, reports, strategies or the like endorsed by DSDIP.

A summary of this process and its intended operation is provided by **Table 3 – Approved Development (Compliance Assessment) Process Summary** and **Figure 4 – Approved Development (Compliance Assessment) Operation**.

TABLE 3 APPROVED DEVELOPMENT (COMPLIANCE ASSESSMENT) PROCESS SUMMARY

Section	What is the content?	When does this section apply?	How does it work?	Who administers the process?	Why is this process needed?
Section 3 For development in accordance with the PoD that is Approved Development subject to Compliance Assessment.	This section is organised by sub-precinct and includes:- ▪ Sub-precinct intent statements; ▪ Uses that are Approved Development subject to Compliance Assessment; ▪ Sub-precinct design criteria; ▪ Criteria for changes to the Reconfiguring a Lot Layout; and ▪ Specific Use Criteria.	Applies to development identified as Approved Development subject to Compliance Assessment in the relevant sub-precinct in Section 3 .	'Compliance Assessment' refers to the assessment process undertaken by DSDIP and administered by way of a Development Approval for a PDA Development Application.	Administered by DSDIP.	This section is intended to facilitate future compliance assessment. Its benefits are:- ▪ a more efficient planning process; ▪ flexibility for Stockland and the community; and ▪ it resolves detailed design and technical requirements




FIGURE 4 APPROVED DEVELOPMENT (COMPLIANCE ASSESSMENT) OPERATION

1.5.2.2.1 Variation to Approved Reconfiguration of a Lot

A RoL is Approved Development (No Further Assessment) where in accordance with plans in Section 2.1 of this PoD.

The following criteria must be met for any variation to the lot layout to be endorsed by DSDIP pursuant to the Approved Development (Compliance Assessment) process set out in **section 1.5.2.2**:

1. Any variation to lot layout must be in accordance with the criteria and plans outlined in **Section 3**;
2. Any variation to lot layout must be accompanied by updated Plans of Development for uses identified in **Section 2.2, Section 2.3, Section 2.5, Section 2.6, Section 2.8 and Section 2.9** as Approved Development (No Further Assessment) which reflect the amended lot layout.

To remove any doubt, it is confirmed that updated Plans of Development endorsed by DSDIP as part of any request to vary the lot layout replace (where applicable) the existing plans and / or controls in **Section 2.2, Section 2.3, Section 2.5, Section 2.6, Section 2.8 and Section 2.9** of this PoD. Development undertaken in accordance with any updated Plan of Development endorsed by DSDIP is taken to be Approved Development (No Further Assessment).

3. The variation must occur before the survey plan is endorsed for the respective stage or super lot;
4. Fixed elements identified by **Sections 3.1 to 3.6** of the PoD cannot be changed or altered by a variation to lot layout.

A request for a variation to the lot layout in a residential village is to be supported by:

- A Short form Planning Report;
- An updated Reconfiguring a Lot Plan for the respective stage of development;
- Updated Plans of Development for uses identified in **Section 2.2, Section 2.3, Section 2.5, Section 2.6, Section 2.8** and **Section 2.9** as Approved Development (No Further Assessment) where affected by the amended lot layout;
- Updated Transport Technical Advice (where relevant);
- Updated Civil, Drainage & WSUD Assessments (where relevant); and
- Demonstration that the variation is consistent with requirements of any Overarching Site Strategy or Infrastructure Mater Plan.

2 Approved Development (No Further Assessment)

This section of the PoD applies to development that is exempt from further assessment where in accordance with the plans and development controls outlined by this section and may proceed to operational works and building works approvals.

The relevant process is further explained by **Section 1 – Explanatory Content** of this PoD. This section of the PoD is relevant to the following:

1. Reconfiguring a Lot;
2. Advertising Devices;
3. Car Park (where associated with Display Home and / or Sales Office);
4. Home Based Business;
5. House or Display Home;
6. Secondary Dwellings
7. Multiple Residential (duplex);
8. Park;
9. Sales Office (where not greater than 400m²)¹;
10. Telecommunications Facility; and
11. Utility Installation

This section includes the following components:

1. Reconfiguring a Lot Plans;
2. Plans and development controls for Advertising Devices;
3. Plans and development controls for a Car Park (where associated with a Display Home and / or Sales Office);
4. Development controls for Home Based Business;
5. Plans and development controls for House or Display Home;
6. Plans and development controls for Multiple Residential (duplex);
7. Development controls for Park;
8. Plans and Development controls for Sales Office (where not greater than 400m²);
9. Plans and development controls for Telecommunications Facility; and
10. Plans and development controls for Utility Installations

2.1 Reconfiguring a Lot

Reconfiguring a Lot plans have been prepared for the Northern Locality – Precinct 2 & Part of Precinct 6 which reflect the proposed lot layout. These plans are included in **Appendix B** and **Appendix C** of the PoD. Reconfiguring a Lot undertaken in accordance with these plans is Approved Development (No Further Assessment) and can proceed to operational works certification and plan sealing.

Section 3 outlines the plans and criteria that apply to any request to vary the lot layout in accordance with the Approved Development (Compliance Assessment) process outlined in **Section 1.5.2.2** of this PoD.

¹ It is noted that a Sales Office, where not greater than 150m² is Exempt development under the Development Scheme

Any variation to lot layout must be accompanied by updated Plans of Development for uses identified in **Section 2.2, Section 2.3, Section 2.5, Section 2.6, Section 2.8 and Section 2.9** as Approved Development (No Further Assessment) to be endorsed by DSDIP.

Updated Plans of Development endorsed by DSDIP as part of any request to vary the lot layout in accordance with the Approved Development (Compliance Assessment) process replace (where applicable) the existing plans and / or controls in **Section 2.2, Section 2.3, Section 2.5, Section 2.6, Section 2.8 and Section 2.9** of this PoD. Development undertaken in accordance with any updated Plan of Development endorsed by DSDIP is taken to be Approved Development (No Further Assessment).

2.2 Advertising Devices

Advertising devices in accordance with the plans and controls in **Table 4 – Advertising Devices Controls** is Approved Development (No Further Assessment) and can proceed to certification of operational works and building works.

Refer to **Section 1 – Explanatory Content** of this PoD for a further explanation.

TABLE 4 – ADVERTISING DEVICES CONTROLS

Advertising Devices Requirements
- Advertising Devices are located and designed generally in accordance with the approved PoD included in Appendix D; OR - Advertising Devices are to be designed generally in accordance with the Planning Scheme requirements as set out in the Development Scheme.

2.3 Car Park (where associated with a Display Home and / or Sales Office)

A Car Park (where associated with a Display Home and / or Sales Office) is Approved Development (No Further Assessment) and can proceed to certification of operational works and building works where:-

- the land is identified as a 'Possible Display Village' or 'Potential Sales Office' as identified on the approved RoL Staging Plan included at **Appendix C**; and
- the use is provided in conjunction with a Display Home and / or Sales Office.

Refer to **Section 1 – Explanatory Content** in this PoD for a further explanation.

2.4 Home Based Business

A Home Based Business is exempt development where the use is in accordance with the provisions of the Home Based Business definition in Schedule 2 of the Caloundra South Urban Development Area Development Scheme.

2.5 House or Display Home

A House or Display Home in accordance with the plans and controls in **Table 5 – House or Display Home Controls** is Approved Development (No Further Assessment) and can proceed to certification of operational works and building works.

Refer to **Section 1 – Explanatory Content** of this PoD for a further explanation.

TABLE 5 – HOUSE OR DISPLAY HOME CONTROLS

House or Display Home Controls
Development for a House or Display Home is generally in accordance with the approved PoD Plans in Appendix E and Appendix F .

2.6 Secondary Dwellings

Secondary Dwellings are Approved Development (no further assessment) provided they meet all of the following criteria:

Secondary Dwelling Controls	
Floor Area of Secondary Dwelling	Maximum 45m ² GFA (Note: GFA excludes the garage and a 4m ² size covered entry porch area only)
Design and Siting of buildings and structures	To be in accordance with the relevant Allotment Diagram in Appendix F. The dwelling/secondary dwelling must have the design effect of one (1) single residential dwelling from the road/street frontage or within public view
Materials and detailing	Materials, detailing, colours and roof form are consistent with those of the primary house
Outdoor Living Space	Minimum 9sq.m with a minimum dimension of 3m and directly accessible from a main living area.
Car Parking and Garaging	Minimum one space – 5m x 3m to be provided within double garage leaving one space to service primary dwelling. No additional garages/covered parking supported
Driveway	Shared minimum driveway with the primary house
Front Entry	If the lot is on a corner – dedicated pedestrian entry and door visible from and addressing the secondary street.
Street Surveillance	On a single street frontage the secondary dwelling entry must be hidden from view from the street so as to give the effect that the home is one (1) single residential dwelling.
Letterboxes	Any Secondary Dwelling is not permitted its own letterbox and must be shared with the primary dwelling.
Titling	Any Secondary Dwelling is unable to be separately titled to the primary dwelling.
Rainwater Tank Requirements	The requirement of a 5000L rainwater tank is to be applied to the dwelling treated as one (1) combined dwelling.
Separate Services	No separate infrastructure servicing to the secondary dwelling is permitted (ie. water, gas, electricity)

2.7 Multiple Residential (duplex)

Multiple Residential (duplex) is Approved Development (No Further Assessment) and can proceed to certification of operational works and building works, where:

- the land is identified as a 'Permissible Multiple Residential (Duplex Lot)' as identified on the approved PoD Plans included at **Appendix E**;
- development is generally in accordance with the approved PoD Plans in **Appendix E** and **Appendix F**;
- each dwelling has an individual design and layout that is not a mirror image of the adjoining dwelling and includes distinct external design elements (e.g. variations in roof line, facade treatment or position of main entrances and garages, window treatments and shading devices).

Refer to **Section 1 – Explanatory Content** in this PoD for a further explanation.

2.8 Park

A Park is exempt development in accordance with Schedule 1 of the Caloundra South Urban Development Area Development Scheme and can proceed to certification of operational works and building works.

2.9 Sales Office

A Sales Office is Approved Development (No Further Assessment) and can proceed to certification of operational works and building works, where:-

- the land is identified as a 'Potential Sales Office Lot' as identified on the approved RoL Staging Plan included at **Appendix C**;
- the use is in accordance with the controls in **Table 6 – Sales Office Controls**.

An ancillary Café (up to a maximum GFA of 120m²) is permitted to be provided in conjunction with the Sales Office provided it is in accordance with the Parking and Access Controls in **Table 6**.

Refer to **Section 1 – Explanatory Content** in this PoD for a further explanation.

TABLE 6 – SALES OFFICE CONTROLS

Sales Office Controls	
Gross Floor Area	The Sales Office has a maximum gross floor area of 400m ² .
Hours of Operation	The hours of operation of the sales office do not commence before 8.00am or extend later than 6.00pm.
Landscaping and Fencing	(a) Private and public open space areas are turfed and landscaped; (b) A 1.8 metre high solid screen fence is provided to each side and rear boundary that has residential uses adjoining.
Temporary Buildings and Structures	Any temporary building or structure associated with the operation of the sales office, or ancillary trade display operating on the subject land is removed from the site within 14 days of the end of the period of operation and the site is left in a clean and tidy condition.
Parking and Access	On site vehicle parking is provided at the rates outlined in Appendix H .
Public Convenience Facilities	If the sales office is in conjunction with a Display Village which comprises 4 or more Display Homes, public toilet facilities are to be provided.

2.10 Telecommunications Facility

A Telecommunications Facility in accordance with the plans and controls in **Table 7 – Telecommunications Facility Controls** is Approved Development (No Further Assessment) and can proceed to certification of operational works and building works.

Refer to **Section 1 – Explanatory Content** of this PoD for a further explanation.

TABLE 7 – TELECOMMUNICATIONS FACILITY CONTROLS

Telecommunications Facilities Requirements
Freestanding Telecommunications facilities are to be designed generally in accordance with the approved PoD plan. The telecommunication tower must be located as it is reflected on the approved PoD plan contained within Appendix G to ensure access to the telecommunication tower is contained wholly within the designated telecommunication tower lot. Access to the telecommunication lot will be facilitated through a separate allotment for access and will provide access to the facility and the conservation buffer.

2.11 Utility Installation

A Utility Installation (Sewer Pump Station and Electrical Transformers) in accordance with the plans and controls in **Table 8 – Utility Installation Controls** is Approved Development (No Further Assessment) and can proceed to certification of operational works and building works. If the proposed is determined to be an Environmentally Relevant Activity, approval will still be required under the *Environmental Protection Regulation 2008*.

Refer to **Section 1 – Explanatory Content** of this PoD for a further explanation.

TABLE 8 – UTILITY INSTALLATION CONTROLS

Utility Installation Requirements
Utility Installations (Sewer Pump Stations) are to be located in accordance with the ROL Plan contained in Appendix B Utility Installations (Electrical Transformers) are to be located and designed generally in accordance with the approved PoD Plan contained within Appendix G.

3 Approved Development (Compliance Assessment)

3.1 Introduction

This section provides the Design Criteria for Approved Development (Compliance Assessment) for development under the process outlined in **Section 1 – Explanatory Content** to this PoD.

The land included within this Plan of Development has been divided into Sub-precincts as shown in **Figure 5 – Sub-Precincts** to facilitate the delivery of sub precinct specific land uses and design criteria.




FIGURE 5 SUB PRECINCTS

This section of the PoD includes the following components for each Sub-Precinct:

1. a statement of overall intent;
2. uses that are Approved Development subject to Compliance Assessment;
3. specific design criteria; and
4. criteria for change to the Reconfiguring a Lot Layout.

This section also includes Compliance Assessment requirements which apply to all Sub-precincts for specific uses.

3.2 Sub-Precinct 2.1 – North Western Neighbourhood and

Sub-Precinct 2.2 – Central Neighbourhood

3.2.1 Sub-Precinct Intent

These sub-precincts comprise a mix of residential development including multiple residential and other

residential, but will comprise **predominantly** detached dwelling product **over a range of lot sizes**. Residential development within the sub-precincts is to target yields of 438 residential allotments within Sub-Precinct 2.1 and 361 residential allotments within Sub-precinct 2.2. Sub-precinct 2.2 commonly referred to as the 'Central Neighbourhood' is intended to reflect an 'Urban Village' concept promoting compact styles of diverse urban living within close proximity to services, employment and centres. The interface of the Urban Village with the District Centre enables increased residential densities proximate to the Centre transitioning to more traditional detached housing product along the east-west sub-arterial link. The Central Neighbourhood provides **for** a sustainable community which prioritises walkability and connectivity providing safe and legible connections to, through and from the Central Neighbourhood to the broader residential neighbourhoods of Precinct 2 and the District Centre.

Small scale non-residential uses are also located throughout the sub-precincts however these uses are of a size which does not compete with the role and function of the District Centre within Sub-precinct 2.8.

The built form of the sub-precinct reflects the residential nature of the area and is low-medium rise. Building design positively contributes to the visual amenity of the sub-precinct, with built form intended to address the street **and** open space **areas (including rear pedestrian linkages)** to promote overlooking and activation of the streetscape and public realm, **and** to ensure casual surveillance is maximised.

The public realm within the sub-precinct comprises a neighbourhood recreation park **located proximate to the highest residential density** in addition to **a network of** local linear parks which provide for passive recreation opportunities for residents **and improved connectivity**. A Lifestyle Buffer is also to be provided along the northern boundary of Sub-precinct 2.1 as a buffer to ecological corridors.

A Display Village is intended to be accommodated within Sub-precinct 2.2 adjoining the Commercial lots. A group of 4 SOHO (Small Office/Home Office) lots are also proposed adjoining the Commercial lots as a transition between the residential and commercial uses.

Vehicular access to the higher order road network within the sub-precinct is limited to a small number of locations to ensure the streets are promoted for use by pedestrians and cyclists. Vehicular access and car parking for non-residential uses ensures its location and design do not create amenity impacts on surrounding residential dwellings.

3.2.2 Uses Subject to Compliance Assessment

The uses that comprise Approved Development subject to Compliance Assessment for Sub-precincts 2.1 and 2.2 are outlined in **Table 9** below.

TABLE 9 – USES FOR SUB-PRECINCTS 2.1 and 2.2

Land Uses
Uses Subject to Compliance Assessment
Multiple Residential (other than duplex) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development. Other residential (retirement living only) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development.
When located where shown in Appendix E – Plan of Development Small Non-residential Nodes and Business as a "Shop/Business and/or Food Premises <250m² GFA": Business:- - up to a maximum of 250m² GFA; and - not extending an existing centre, approved Business, Food premises or Shop.

Land Uses
- Food Premises:- - up to a maximum of 250m² GFA; and - not extending an existing centre, approved Business, Food premises or Shop. - Shop:- - up to a maximum of 250m² GFA; and - not extending an existing centre, approved Business, Food premises or Shop.
When located where shown in Appendix E – Plan of Development Small Non-Residential Nodes and Business as a “SOHO Lot – Business or Shop” Lot: - Business:- - The Business use does not comprise a Veterinarian Clinic; - The maximum Gross Floor Area of the Business use is 90m²; and - The Business use is conducted on that part of the site fronting Commercial Lot 80001 only. - Shop:- - The Shop use does not involve betting; - The maximum Gross Floor Area of the Shop use is 90m²; and - The Shop use is conducted on that part of the site fronting Commercial Lot 80001 only.

3.2.3 Specific Design Criteria

Applications for Compliance Assessment in Sub-precincts 2.1 and 2.2 are required to be assessed against and fulfil the Design Standards identified in **Table 10**.

TABLE 10 – DESIGN STANDARDS FOR SUB PRECINCTS 2.1 AND 2.2

Element	Design Standard
USE	DS1.1 Land uses comprise the uses specified for the sub-precinct in Table 9. DS1.2 In addition to the following Sub-precinct design standards, the use is in accordance with the relevant provisions of Section 3.9 Specific Use Criteria.
DESIGN	DS2.1 For those lots shown as “SOHO Lot – Business or Shop” within Appendix E – Plan of Development Small Non-Residential Nodes and Business, the building is designed in accordance with the Plan of Development for SOHO lots (Appendix F).
PARKING AND ACCESS	DS3.1 On site vehicle parking is provided at the rates outlined in Appendix H (with the exception of the SOHO Lots). DS3.2 For those lots shown as “SOHO Lot – Business or Shop” within Appendix E – Plan of Development Small Non-Residential Nodes and Business, on site vehicle parking is provided at the rates outlined in Appendix H, or if on-site parking cannot be achieved for the Business or Shop use, parking for this component of the use is secured within the easement contained within the adjoining Commercial Lot 80001, prior to commencement of the Business or Shop use.

Element	Design Standard
	DS3.3 Where possible, development provides for shared or multiple use of car parking areas, particularly large car parking areas:- (a) at times when car parking areas would otherwise not be occupied (e.g. weekends); and (b) when car parking spaces service two or more land uses with varying peak usage times (e.g. restaurants and entertainment uses which generate peak parking demands in periods when retail or office uses are relatively inactive).
ENVIRONMENT	DS4.1 All rainwater tanks to residential dwellings are designed to ensure that 50% of rainwater is captured from the roof, to the purpose of supplying water to toilets, laundry, and have a connection for external usage. DS4.2 All rain tanks to residential dwellings are to be a minimum 5,000 litres capacity for detached houses and a minimum 3,000 litres capacity for semi-attached and attached houses. DS4.3 All rainwater tanks to non-residential buildings are designed to ensure 75% roof capture and reuse, with collected water used for all suitable applications within the property. DS4.4 For non-residential sites, each site will need to demonstrate how they will satisfy standard best practice pollutant load removal targets (i.e. 80%, 60%, 45% and 90% removal of the average annual loads for total suspended solids, total phosphorus, total nitrogen, and gross pollutants). A range of stormwater quality management measures (e.g. bioretention) could be applied to comply with these targets. As part of the stormwater quality management strategy for each site, rainwater tanks will also need to be installed to collect roof runoff from a minimum 75% of the roof area – with captured roofwater used to supplement non-potable water demands.
INFRASTRUCTURE	D5.1 All development is connected to the reticulated water supply, sewerage, stormwater drainage and telecommunications infrastructure networks and has an electricity supply.

3.2.4 Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precincts 2.1 and 2.2

Applications for Compliance Assessment to vary the lot layout in Sub-precincts 2.1 and / or 2.2 must be in accordance with the Plans and Design Standards outlined in this section.

Figure 6 identifies those fixed elements of the PoD that cannot be adversely impacted or changed. **Table 11** identifies the applicable Design Standards for a lot layout in Sub-precinct 2.1 and **Table 12** identifies the applicable Design Standards for a lot layout in Sub-precinct 2.2.




FIGURE 6 – SUB PRECINCTS 2.1 and 2.2 FIXED ELEMENTS

TABLE 11 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.1

Design Standards	
Number of Local/Neighbourhood Parks	1 Neighbourhood Park
Total Neighbourhood Park Area Required	0.5 ha
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 6 .
Maximum Yield (+/- 10%)	438 dwellings
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. Width in multiples of 2.5 metres and 5.0 metres consistent with typical lot dimensions. - Urban lots are a typical depth of 13.5 – 15.0 metres. Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop

Design Standards	
Street Network	• Grid pattern or modified grid responsive to site characteristics. • Where slope allows, orientation within 15 degrees of north-south or east-west. • Connector and main streets of centres orientated to landmarks. • To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. • Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.
Streets	Street network includes: • A trunk connector providing access to neighbourhood connector streets; • Neighbourhood connector streets providing connections to neighbourhood destinations; • Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and • Neighbourhood lanes – provide direct property access either at the front or rear of lots.
Typical Road Typologies and Cross Sections	Roads are designed generally in accordance with Appendix K .
Carparking	One room or one bedroom house • 0.5 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit. Two or more bedroom house • 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: • The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or • The development secures a higher proportion of on-site parking
PDA Guidelines and Practice Notes	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014)

Design Standards	
	PDA Practice Note No. 11 - Parking Analysis Plans (July 2012)
	PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)

TABLE 12 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.2

Design Standards	
Number of Local/Neighbourhood Parks	1 Neighbourhood Park
Total Neighbourhood Park Area Required	0.5 ha
Maximum Yield (+/- 10%)	366 dwellings
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. - Urban lots are a typical depth of 13.5 – 15.0 metres Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater.
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row unless serviced by a rear lane. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).

Design Standards	
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop
Street Network	- Grid pattern or modified grid responsive to site characteristics. - Where slope allows, orientation within 15 degrees of north-south or east-west. - Connector and main streets of centres orientated to landmarks. - To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. - Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.
Streets	Street network includes: - A trunk connector providing access to neighbourhood connector streets; - Neighbourhood connector streets providing connections to neighbourhood destinations; - Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and - Neighbourhood lanes – provide direct property access either at the front or rear of lots.
Typical Road and Cross Sections	Roads are designed generally in accordance with Appendix K .
Carparking	One room or one bedroom house 0.5 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit. Two or more bedroom house 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: - The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or - The development secures a higher proportion of on-site parking
PDA Guidelines and Practice Notes	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014)

Design Standards	
	PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014) PDA Practice Note No. 11 - Parking Analysis Plans (July 2012) PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)

3.3 Sub-Precinct 2.3 – South Western Neighbourhood,

Sub-Precinct 2.4 – Southern Neighbourhood,

Sub-Precinct 2.5 – South East Premium Neighbourhood and

Sub-Precinct 2.6 – South Eastern Neighbourhood

3.3.1 Sub-Precinct Intent

These sub-precincts comprise a mix of residential development including multiple residential, other residential and live-work opportunities, but will comprises predominantly of detached dwelling houses. Residential development with the sub-precincts is to target yields of 311 residential allotments within Sub-precinct 2.3, 191 residential allotments within Sub-Precinct 2.4, 196 residential allotments within Sub-precinct 2.5 and 86 residential allotments within sub-precinct 2.6.

Small scale non-residential uses are also located throughout the sub-precincts however these uses are of a size which does not compete with the role and function of the District Centre within Sub-precinct 2.8.

The built form of the sub-precinct reflects the residential nature of the area and is low-medium rise. Building design positively contributes to the visual amenity of the sub-precinct, with built form addressing the street and promoting overlooking of the street to maximise casual surveillance.

Public realm within the sub-precincts comprises three Neighbourhood Parks located throughout the residential neighbourhoods which provide for passive recreation opportunities. A community garden is proposed within sub-precinct 2.3 park to provide places for learning and sharing about sustainable living practices for residents. A lifestyle buffer is also provided along the southern edge of Sub-precincts 2.3, 2.4 and 2.5 to act as a buffer to the Bells Creek North to provide a buffer to ecological corridors. A further linear park/drainage corridor is provided along the western boundary of sub-precinct 2.3 which also provides a physical buffer to the Bells Creek Arterial.

Vehicular access to the higher order road network within the sub-precinct is limited to a small number of locations to ensure the streets are promoted for use by pedestrians and cyclists. Vehicular access and car parking for non-residential uses ensures its location and design do not create amenity impacts on surrounding residential dwellings.

3.3.2 Uses subject to Compliance Assessment

The uses that comprise Approved Development subject to Compliance Assessment for sub-precincts 2.3, 2.4, 2.5 and 2.6 are outlined in **Table 13** below.

TABLE 13 – USES FOR SUB-PRECINCTS 2.3, 2.4, 2.5 AND 2.6

Land Uses
Uses Subject to Compliance Assessment
Multiple Residential (other than duplex) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development. Other residential (retirement living only) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development.
When located where shown in Appendix E – Plan of Development Small Non-residential Nodes and Business:- • Business:- - up to a maximum of 250m² GFA; and - not extending an existing centre, approved Business, Food premises or Shop. • Food Premises:- - up to a maximum of 250m² GFA; and - not extending an existing centre, approved Business, Food premises or Shop. • Shop:- - up to a maximum of 250m² GFA; and - not extending an existing centre, approved Business, Food premises or Shop.

3.3.3 Specific Design Criteria

Applications for Compliance Assessment in Sub-Precincts 2.3, 2.4, 2.5 and 2.6 are required to be assessed against and fulfil the Design Standards identified in **Table 14**.

TABLE 14 – DESIGN STANDARDS FOR SUB PRECINCTS 2.3, 2.4, 2.5 AND 2.6

Element	Design Standard
USE	DS1.1 Land uses comprise the uses specified for the sub-precinct in Table 13. DS1.2 In addition to the following Sub-precinct design standards, the use is in accordance with the relevant provisions of Section 3.9 Specific Use Criteria.
PARKING AND ACCESS	DS2.1 On site vehicle parking is provided at the rates outlined in Appendix H. DS2.2 Where possible, development provides for shared or multiple use of car parking areas, particularly large car parking areas:- (a) at times when car parking areas would otherwise not be occupied (e.g. weekends); and (b) when car parking spaces service two or more land uses with varying peak usage times (e.g. restaurants and entertainment uses which generate peak parking demands in periods when retail or office uses are relatively inactive).

Element	Design Standard
ENVIRONMENT	DS3.1 All rainwater tanks to residential dwellings are designed to ensure that 50% of rainwater is captured from the roof, to the purpose of supplying water to toilets, laundry, and have a connection for external usage. DS3.2 All rain tanks to residential dwellings are to be a minimum 5,000 litres capacity for detached houses and a minimum 3,000 litres capacity for semi-attached and attached houses DS3.3 All rainwater tanks to non-residential buildings are designed to ensure 75% roof capture and reuse, with collected water used for all suitable applications within the property. DS3.4 For non residential sites, each site will need to demonstrate how they will satisfy standard best practice pollutant load removal targets (i.e. 80%, 60%, 45% and 90% removal of the average annual loads for total suspended solids, total phosphorus, total nitrogen, and gross pollutants). A range of stormwater quality management measures (e.g. bioretention) could be applied to comply with these targets. As part of the stormwater quality management strategy for each site, rainwater tanks will also need to be installed to collect roof runoff from a minimum 75% of the roof area – with captured roofwater used to supplement non-potable water demands.
INFRASTRUCTURE	D4.1 All development is connected to the reticulated water supply, sewerage, stormwater drainage and telecommunications infrastructure networks and has an electricity supply.

3.3.4 Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precincts 2.3, 2.4, 2.5 and 2.6

Applications for Compliance Assessment to vary the lot layout in Sub-precincts 2.3, 2.4, 2.5 and / or 2.6 must be in accordance with the Plans and Design Standards outlined in this section.

Figure 7 identifies those fixed elements of the PoD that cannot be adversely impacted or changed. **Table 15** identifies the applicable Design Standards for a lot layout in Sub-precinct 2.3, **Table 16** identifies the applicable Design Standards for a lot layout in Sub-precinct 2.4, **Table 17** identifies the applicable Design Standards for a lot layout in Sub-precinct 2.5 and **Table 18** identifies the applicable Design Standards for a lot layout in Sub-precinct 2.6.




FIGURE 7 – SUB PRECINCTS 2.3, 2.4, 2.5 AND 2.6 FIXED ELEMENTS

TABLE 15 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.3

Design Standards	
Number of Local/Neighbourhood Parks	1 Neighbourhood Park
Total Neighbourhood Park Area Required	0.5ha
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 7 .
Maximum Yield (+/- 10%)	311 dwellings
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. Width in multiples of 2.5 metres and 5.0 metres consistent with typical lot dimensions - Urban lots are a typical depth of 13.5 – 15.0 metres

Design Standards	
	Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop
Street Network	- Grid pattern or modified grid responsive to site characteristics. - Where slope allows, orientation within 15 degrees of north-south or east-west. - Connector and main streets of centres orientated to landmarks. - To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. - Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.
Streets	Street network includes: - A trunk connector providing access to neighbourhood connector streets; - Neighbourhood connector streets providing connections to neighbourhood destinations; - Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and - Neighbourhood lanes – provide direct property access either at the front or rear of lots.
Typical Typologies and Cross Sections	Roads are designed generally in accordance with Appendix K .
Carparking	One room or one bedroom house 0.5 on-street parking space per house/dwelling unit is provided within

Design Standards	
	reasonable proximity of the house/dwelling unit. Two or more bedroom house 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: - The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or - The development secures a higher proportion of on-site parking
PDA Guidelines and Practice Notes	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014) PDA Practice Note No. 11 - Parking Analysis Plans (July 2012) PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)

TABLE 16 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.4

Design Standards	
Number of Local/Neighbourhood Parks	1 Local Park
Total Local Recreation Park Area Required	0.3ha
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 7 .
Maximum Yield (+/- 10%)	190 dwellings

Design Standards	
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. Width in multiples of 2.5 metres and 5.0 metres consistent with typical lot dimensions - Urban lots are a typical depth of 13.5 – 15.0 metres Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop
Street Network	- Grid pattern or modified grid responsive to site characteristics. - Where slope allows, orientation within 15 degrees of north-south or east-west. - Connector and main streets of centres orientated to landmarks. - To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. - Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.
Streets	Street network includes: - A trunk connector providing access to neighbourhood connector streets; - Neighbourhood connector streets providing connections to neighbourhood destinations; - Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and - Neighbourhood lanes – provide direct property access either at the front or rear of lots.

Design Standards		
Typical Typologies Cross Sections	Road and	Roads are designed generally in accordance with Appendix K .
Carparking		One room or one bedroom house • 0.5 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit. Two or more bedroom house • 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: • The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or • The development secures a higher proportion of on-site parking
PDA Guidelines and Practice Notes		PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014) PDA Practice Note No. 11 - Parking Analysis Plans (July 2012) PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)

TABLE 17 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.5

Design Standards	
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 7 .
Maximum Yield (+/- 10%)	196 dwellings
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. Width in multiples of 2.5 metres and 5.0 metres consistent with typical lot dimensions - Urban lots are a typical depth of 13.5 – 15.0 metres Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop
Street Network	- Grid pattern or modified grid responsive to site characteristics. - Where slope allows, orientation within 15 degrees of north-south or east-west. - Connector and main streets of centres orientated to landmarks. - To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. - Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.

Design Standards	
Streets	Street network includes: • A trunk connector providing access to neighbourhood connector streets; • Neighbourhood connector streets providing connections to neighbourhood destinations; • Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and • Neighbourhood lanes – provide direct property access either at the front or rear of lots.
Typical Road Typologies and Cross Sections	Roads are designed generally in accordance with Appendix K .
Carparking	One room or one bedroom house • 0.5 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit. Two or more bedroom house • 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: • The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or • The development secures a higher proportion of on-site parking
PDA Guidelines and Practice Notes	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014) PDA Practice Note No. 11 - Parking Analysis Plans (July 2012) PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)

TABLE 18 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.6

Design Standards	
Number of Local/Neighbourhood Parks	1 Neighbourhood Parks
Total Neighbourhood Park Area Required	0.5ha
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 7 .
Maximum Yield (+/- 10%)	86 dwellings
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. Width in multiples of 2.5 metres and 5.0 metres consistent with typical lot dimensions - Urban lots are a typical depth of 13.5 – 15.0 metres Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop.

Design Standards	
Street Network	• Grid pattern or modified grid responsive to site characteristics. • Where slope allows, orientation within 15 degrees of north-south or east-west. • Connector and main streets of centres orientated to landmarks. • To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. • Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.
Streets	Street network includes: • A trunk connector providing access to neighbourhood connector streets; • Neighbourhood connector streets providing connections to neighbourhood destinations; • Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and • Neighbourhood lanes – provide direct property access either at the front or rear of lots.
Typical Road and Cross Sections	Roads are designed generally in accordance with Appendix K .
Carparking	One room or one bedroom house • 0.5 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit. Two or more bedroom house • 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: • The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or • The development secures a higher proportion of on-site parking
PDA Guidelines and Practice Notes	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014) PDA Practice Note No. 11 - Parking Analysis Plans (July 2012)

Design Standards	
	PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)

3.4 Sub-Precinct 2.7 – The Pocket

3.4.1 Sub-Precinct Intent

This sub-precinct offers a unique opportunity for a boutique, eco friendly, development that takes advantage of its distinct location. It is anticipated that development is likely to consist of detached dwelling houses; however, opportunities to deliver this sub-precinct as a multiple residential or other residential development through a community title arrangement are also afforded.

Residential yield within this sub-precinct is to target a minimum of 94 dwellings, and built form is to be low-medium rise and respect the environmental characteristics of the surrounding landscape.

Non-residential land uses are not otherwise consistent with the outcomes sought for this sub-precinct.

Vehicular access to the street within the sub-precinct ensures that the streets are promoted for use by pedestrians and cyclists.

3.4.2 Uses Subject to Compliance Assessment

The uses that comprise Approved Development subject to Compliance Assessment for Sub-precinct 2.7 are outlined in **Table 19** below.

TABLE 19 – USES FOR SUB-PRECINCTS 2.7

Land Uses
Uses Subject to Compliance Assessment
Multiple Residential (other than duplex) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development. Other residential (retirement living only) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development.

3.4.3 Specific Design Criteria

Applications for Compliance Assessment in Sub-Precinct 2.7 are required to be assessed against and fulfil the Design Standards identified in **Table 20**.

TABLE 20 – DESIGN STANDARDS FOR SUB PRECINCT 2.7

Element	Design Standard
USE	DS1.1 Land uses comprise the uses specified for the sub-precinct in Table 19. DS1.2 In addition to the following Sub-precinct design standards, the use is in accordance with the relevant provisions of Section 3.9 Specific Use Criteria.

PARKING AND ACCESS	DS2.1 On site vehicle parking is provided at the rates outlined in Appendix H .
ENVIRONMENT	DS3.1 All rainwater tanks to residential dwellings are designed to ensure that 50% of rainwater is captured from the roof, to the purpose of supplying water to toilets, laundry, and have a connection for external usage. DS3.2 All rain tanks to residential dwellings are to be a minimum 5,000 litres capacity for detached houses and a minimum 3,000 litres capacity for semi-attached and attached houses
INFRASTRUCTURE	D4.1 All development is connected to the reticulated water supply, sewerage, stormwater drainage and telecommunications infrastructure networks and has an electricity supply.

3.4.4 Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 2.7

Applications for Compliance Assessment to vary the lot layout in Sub-precinct 2.7 must be in accordance with the Plans and Design Standards outlined in this section.

Figure 8 identifies those fixed elements of the PoD that cannot be adversely impacted or changed. **Table 21** identifies the applicable Design Standards for a lot layout.




FIGURE 8 – SUB PRECINCTS 2.7 FIXED ELEMENTS

TABLE 21 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.7

Design Standards	
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 8 .
Maximum Yield (+/- 10%)	94 dwellings
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. Width in multiples of 2.5 metres and 5.0 metres consistent with typical lot dimensions - Urban lots are a typical depth of 13.5 – 15.0 metres Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop
Street Network	- Grid pattern or modified grid responsive to site characteristics. - Where slope allows, orientation within 15 degrees of north-south or east-west. - Connector and main streets of centres orientated to landmarks. - To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. - Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.

Design Standards	
Streets	Street network includes: • A trunk connector providing access to neighbourhood connector streets; • Neighbourhood connector streets providing connections to neighbourhood destinations; • Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and • Neighbourhood lanes – provide direct property access either at the front or rear of lots.
Typical Road Typologies and Cross Sections	Roads are designed generally in accordance with Appendix K .
Carparking	One room or one bedroom house • 0.5 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit. Two or more bedroom house • 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: • The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or • The development secures a higher proportion of on-site parking
PDA Guidelines and Practice Notes	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014) PDA Practice Note No. 11 - Parking Analysis Plans (July 2012) PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)

3.5 Sub-Precinct 2.8 – District Centre

3.5.1 Sub-Precinct Intent

This sub-precinct comprises an integrated mix of land uses, including retail, community uses and residential development that form a District Centre for the Northern Locality of Caloundra South. Development is of a compact urban form that serves as a focal point for community life and incorporates an active street, higher density residential development and a potential retirement village. The sub-precinct accommodates up to a maximum of 8,000m² of retail gross floor area and 4,000m² of commercial gross floor area.

The ability to reconfigure land in this sub-precinct is afforded to facilitate the delivery of more manageable development lots that offer distinct development opportunities. Notwithstanding the ability to reconfigure land in this sub-precinct, design outcomes intended for this sub-precinct will be required to be achieved.

The public realm within this sub-precinct is defined by key elements which include:-

- Main Street – this active street connects the key elements of this sub-precinct and its surrounds;
- Town Square – the Town Square is a minimum size of 500m² and is located adjacent the dedicated community use site in the north east of the sub-precinct. The civic square is located such that it offers opportunities for active uses such as markets.

The built form of the sub-precinct achieves a vibrant urban form delivered through a scale of development that defines the active street network. Development provides an active frontage to the Main Street and Civic Square.

Community facilities in the sub-precinct include a community site co-located with the P – 6 (Prep to Grade 6) Primary School in Sub-Precinct 2.9. A Community Garden may be established on the community site to provide a communal space for residents and visitors to the district centre for learning and sharing about sustainable living practices. It is also anticipated that occasional community events and concerts will occur within the sub-precinct.

Sub-precinct 2.8 directly adjoins a proposed Display Village. Land at the western end of the sub-precinct may be used to accommodate a Temporary Sales Office, Café, car parking and an informal play area for use in conjunction with the adjoining Display Village, until such time as the Display Village is no longer required and the land is developed for its intended permanent use in accordance with this PoD.

Vehicle access to this sub-precinct is gained from the surrounding street network and is focused on key locations to consolidate access points.

3.5.2 Uses Subject to Compliance Assessment

The uses that comprise Approved Development subject to Compliance Assessment for sub-precinct 2.8 are outlined in **Table 22** below.

TABLE 22 – USES FOR SUB-PRECINCT 2.8

Land Uses	
Uses Subject to Compliance Assessment	
On Lot 80000 and 80001	
Business	Market
Car park (other than a multi-level facility) where incorporating landscaping along the sites boundaries to enhance the visual appeal	Multiple Residential (other than duplex)
Display unit	Place of Assembly, where maximum 500m ² GFA
Emergency Services	Service Industry where: - not adjoining residential uses;

Land Uses	
Fast Food Premises, where: - not adjoining a residential use; and - not including a drive through. Food Premises Health care services Indoor Entertainment (Tavern / Hotel only) Indoor Sport and Recreation, where excluding premises for conducting large scale functions, i.e. convention centre, amusement and leisure centres	- maximum 500m² GFA Shop Shopping Centre Short-term accommodation Showroom Telecommunications facility, where: - integrated within a building; - not located adjoining the Urban Living Land Use Area Utility installation, where; - integrated within a building; - not located adjoining the Urban Living Land Use Area Veterinary Hospital
On Lot 80002	
Multiple Residential (other than duplex) Outdoor Sport and Recreation limited to temporary drive-in theatre Short-term accommodation Indoor Sport and Recreation, where excluding premises for conducting large scale functions, i.e. convention centre, amusement and leisure centres Child care centre	
On Lot 80012	
Child care centre	
On Lot 80004	
Community Facility Health care services Emergency Services Market Place of Assembly, where maximum 500m² GFA	

3.5.3 Specific Design Criteria

Applications for Compliance Assessment in Sub-Precinct 2.8 are required to be assessed against and fulfil the Design Standards identified in **Table 23**.

TABLE 23 – DESIGN STANDARDS FOR SUB PRECINCT 2.8

Element	Design Standard
USE	DS1.1 Land uses comprise the uses specified for the sub-precinct in Table 22. DS1.2 In addition to the following Sub-precinct design standards, the use is in accordance with the relevant provisions of Section 3.9 Specific Use Criteria.
BUILT FORM	DS2.1 The gross floor area (GFA) of retail uses does not exceed 8,000m². DS2.2 The GFA of commercial uses does not exceed 4,000m². DS2.3 Residential development does not exceed:- (a) 20 dwellings on the district centre commercial lots as shown on the approved RoL Plans at Appendix B and Appendix C; and (b) 68 dwellings on the mixed use site as shown on the approved RoL Plans at Appendix B and Appendix C. DS3.1 For all development, building height does not exceed 5 storeys. DS4.1 Development is generally in accordance with the approved PoD as contained within Appendix I, and meets the following: (a) site cover for commercial and retail uses is to be dictated by compliance with set backs, landscaping and parking requirements of this PoD. Delivery facilities are also to be provided which may be a shared arrangement between uses; and (b) the District Centre provides an area suitable to accommodate public event spaces which cater to a variety of audiences. DS4.2 Development within Lot 80001 for a Temporary Sales Office, Café, car parking and informal park is to be in accordance with the approved “PoD – Temporary Sales & Display Villages” as contained within Appendix I. All other Design Standards contained within this table do not apply to the temporary uses, with the exception of the following Elements: Parking and Access, Environment and Infrastructure. DS5.1 Built form setbacks are generally in accordance with the following:- (a) Maximum podium height – 2 storeys; (b) Street setbacks (minimum):- (i) Required building frontage where nominated on the district centre sites on the approved PoD at Appendix I – 0 metres, except where also nominated on the approved PoD as Visual screening of required loading area / back of house; (ii) Required building frontage where nominated on the mixed use site on the approved PoD at Appendix I – 0 to 3 metres, except where also nominated on the approved PoD as a Landscape setback; (iii) Desired building frontage where nominated on the approved PoD at Appendix I – 0 to 1.5 metres for non-residential elements and 1.5 to 3.0 metres for residential elements, except where:- a. also nominated on the approved PoD as Visual screening of required loading area / back of house, in which case a minimum setback of 1.5 metres applies;

Element	Design Standard
	(iv) Landscape setback where nominated on the approved PoD at Appendix I – 3 metres with building articulation. (c) Side setbacks (minimum):- (i) Levels 1–3 – 0 metres where adjoining a non-residential use or the minimum setback on the adjoining boundary is 0 metres, otherwise:- 1.5m for a wall up to 4.5m high; 2.0m for a wall up to 7.5m high; 2m plus 0.5m for every 3m (or part thereof) over 7.5m high for a wall over 7.5m high, except that a wall may be built to a side boundary where the wall has a maximum height of 3m and a maximum length of 15m, unless it abuts a higher or longer existing or simultaneously constructed wall. (ii) Levels 4–5 – 3 metres. (d) Rear setbacks:- (i) Levels 1–3 – 0 metres where adjoining a non-residential use or the minimum setback on the adjoining boundary is 0 metres, otherwise 3m; (ii) Levels 4–5 – 6 metres. DS6.1 Sub-tropical design elements are incorporated within building design, including but not limited to: - the maximising of natural light and cross-ventilation; - the provision of fixed and adjustable sun shading devices to control direct solar access; and - the provision of roof eave overhangs to walls, wall openings and balconies; - provision of awnings or shading devices over active street frontages and key pedestrian thoroughfares within the site; - provision of outdoor and on-street dining opportunities particularly onto the civic square, main street, entry street and esplanade street as defined in the approved PoD in Appendix I. Such dining areas should occupy the northern, eastern or civic square frontages of the site. DS7.1 Where a Required building frontage (and not otherwise also nominated as having a Visual screening of required loading area / back of house) is identified on the district centre sites on the approved PoD contained in Appendix I, shop fronts and facades are built to the front boundary and provide the following; - an awning extending over the street verge. Such awnings must extend a minimum of 1.5m and may extend up to 3.0m over the street verge and may include cut-outs to allow for street tree growth; - visual connectivity to the street for customers and patrons. This street activation is achieved by maximising glazing, entrances, or open dining areas. Blank facades and back of house building elements are not to occupy these frontages. DS8.1 Development on a corner site identified on the approved PoD as contained within Appendix I as Desired built form on this corner provides:- - buildings built to frame the street; - windows and apertures face the street; - awnings and public realm treatments at the ground plan to celebrate the corner and contribute to the public realm. DS9.1 Where Residential uses are proposed on the district centre commercial Lot, they are located generally in accordance with the approved PoD as contained

Element	Design Standard
	within Appendix I. DS9.2 Where Commercial and / or Community uses are proposed on the mixed use lot they are located generally in accordance with the approved PoD as contained within Appendix I. DS9.3 Development of an <i>Outdoor Sport and Recreation (limited to temporary drive-in theatre)</i> is limited to the mixed use lot as shown on the approved PoD as contained within Appendix I and shall incorporate landscaping along the sites boundaries to enhance the visual appeal. Design standards for permanent uses do not apply for an <i>Outdoor Sport and Recreation (limited to temporary drive-in theatre)</i>. Further design standards for this use is specified in DS 36.6.
PUBLIC REALM	DS10.1 Development provides for a minimum area of landscaping and recreation space generally in accordance with the following:- (a) For Residential elements – a minimum of 30% of the site area including 5% of site area as deep planting; (b) For Non-Residential elements – 20% of the site area including 5% of site area as deep planting. DS10.2 Landscaping:- (a) shall be to a high standard sufficient to soften built edges and break up the visual mass of internal parking and circulation areas, reduce heat gain on hard surfaces, and enhance microclimate within the centre; (b) should integrate in design and plant species with that provided within the surrounding street network and the adjoining parkland. Public spaces and footpaths are to be provided with shade trees and furniture; (c) is to integrate with the Civic Square and open space areas to the north, and is to be designed in accordance with the approved Landscape Master Plan. DS10.3 Public realm should be provided with adequate lighting for safety. Care should be taken with lighting design to ensure that nearby residences are not affected by 'overspill'. DS11.1 A Town Square with a minimum size of 500m² is located as shown on the approved PoD as contained within Appendix I. DS12.1 Interfaces and streetscapes are developed generally in accordance with the approved PoD as contained within Appendix I.
PARKING ACCESS AND	DS14.1 Site access points for vehicles are located generally as shown on the approved PoD, included in Appendix I. DS14.2 On-site at-grade car parking areas are located generally in the locations identified as At grade car parks on the approved PoD, included at Appendix I. DS14.3 On-site at-grade car parking areas are generally screened from view from surrounding streets by a combination of built form and planted buffers. DS14.4 Primary vehicle circulation is provided generally in accordance with the Internal vehicle circulation route as shown on the approved PoD as contained within Appendix I.

Element	Design Standard																																															
	DS14.5 Loading and Service Areas are generally located and screened as shown on the approved PoD, as contained within Appendix I. DS14.6 An easement for access and car parking purposes is to be provided within Lot 80001, for use by the adjoining SOHO Lots 1-4. This easement is to accommodate vehicle access for Lot 80001 as well as parking for the visitors of the SOHO Lots in accordance with the approved PoD as contained within Appendix I.																																															
	DS15.1 Shade trees shall be planted in on-site car parks at a rate of one (1) tree per six (6) car parking spaces.																																															
	DS16.1 Bicycle parking spaces must be provided in accordance with AUSTROADS Part 14 and AS2890.3 Parking Facilities, Part 3: Bicycle Parking Facilities. DS16.2 Bicycle parking is provided at the rates outlined in Appendix H. DS16.3 End of trip facilities for bicycles, involving dedicated amenities that are publicly accessible for bike storage areas, lockers, toilets and change facility, must be provided on the district centre commercial lot as shown on the approved PoD included at Appendix I at the following rates:- <table><tr><th>Lockers, change rooms, showers, sanitary compartments and washbasins</th><th>Bicycle parking spaces</th><th>Personal lockers</th><th>User group</th><th>Change rooms</th><th>Showers</th><th>Sanitary compartments</th><th>Wash basins</th></tr><tr><td rowspan="6"></td><td>1 – 5</td><td>1 / space</td><td>Female and Male</td><td>1 of unisex design</td><td>1</td><td>1 closet pan</td><td>1</td></tr><tr><td rowspan="2">6 – 19</td><td rowspan="2">1 / space</td><td>Female</td><td>1</td><td>1</td><td>1 closet pan</td><td>1</td></tr><tr><td>Male</td><td>1</td><td>1</td><td>1 closet pan</td><td>1</td></tr><tr><td rowspan="2">20 or more</td><td rowspan="2">1 / space</td><td>Female</td><td>1</td><td>1 plus 1 additional for every 20 bicycle parking spaces thereafter</td><td>2 closet pans plus 1 additional for every 60 bicycle parking spaces thereafter</td><td>1 plus 1 additional for every 60 bicycle parking spaces thereafter</td></tr><tr><td>Male</td><td>1</td><td>1 plus 1 additional for every 20 bicycle parking spaces thereafter</td><td>2 closet pans plus 1 additional for every 60 bicycle parking spaces thereafter</td><td>1 plus 1 additional for every 60 bicycle parking spaces thereafter</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Lockers, change rooms, showers, sanitary compartments and washbasins	Bicycle parking spaces	Personal lockers	User group	Change rooms	Showers	Sanitary compartments	Wash basins		1 – 5	1 / space	Female and Male	1 of unisex design	1	1 closet pan	1	6 – 19	1 / space	Female	1	1	1 closet pan	1	Male	1	1	1 closet pan	1	20 or more	1 / space	Female	1	1 plus 1 additional for every 20 bicycle parking spaces thereafter	2 closet pans plus 1 additional for every 60 bicycle parking spaces thereafter	1 plus 1 additional for every 60 bicycle parking spaces thereafter	Male	1	1 plus 1 additional for every 20 bicycle parking spaces thereafter	2 closet pans plus 1 additional for every 60 bicycle parking spaces thereafter	1 plus 1 additional for every 60 bicycle parking spaces thereafter							
Lockers, change rooms, showers, sanitary compartments and washbasins	Bicycle parking spaces	Personal lockers	User group	Change rooms	Showers	Sanitary compartments	Wash basins																																									
	1 – 5	1 / space	Female and Male	1 of unisex design	1	1 closet pan	1																																									
	6 – 19	1 / space	Female	1	1	1 closet pan	1																																									
			Male	1	1	1 closet pan	1																																									
	20 or more	1 / space	Female	1	1 plus 1 additional for every 20 bicycle parking spaces thereafter	2 closet pans plus 1 additional for every 60 bicycle parking spaces thereafter	1 plus 1 additional for every 60 bicycle parking spaces thereafter																																									
			Male	1	1 plus 1 additional for every 20 bicycle parking spaces thereafter	2 closet pans plus 1 additional for every 60 bicycle parking spaces thereafter	1 plus 1 additional for every 60 bicycle parking spaces thereafter																																									
	DS17.1 On site vehicle parking is provided at the rates outlined in Appendix H.																																															
	DS18.1 Where possible, development provides for shared or multiple use of car parking areas, particularly large car parking areas:- (a) at times when car parking areas would otherwise not be occupied (e.g. weekends); and (b) when car parking spaces service two or more land uses with varying peak usage times (e.g. restaurants and entertainment uses which generate peak parking demands in periods when retail or office uses are relatively inactive).																																															
	DS19.1 The internal carpark required by the approved PoD Plans in Appendix I is landscaped with shade trees and planting beds and edges.																																															
ENVIRONMENT	DS20.1 All rainwater tanks to residential dwellings are designed to ensure that 50% of rainwater is captured from the roof, to the purpose of supplying water to toilets,																																															

Element	Design Standard
	laundry, and have a connection for external usage. DS20.2 All rain tanks to residential dwellings are to be a minimum 5,000 litres capacity for detached houses and a minimum 3,000 litres capacity for semi-attached and attached houses DS20.3 All rainwater tanks to non-residential buildings are designed to ensure 75% roof capture and reuse, with collected water used for all suitable applications within the property. DS20.4 For non residential sites, each site will need to demonstrate how they will satisfy standard best practice pollutant load removal targets (i.e. 80%, 60%, 45% and 90% removal of the average annual loads for total suspended solids, total phosphorus, total nitrogen, and gross pollutants). A range of stormwater quality management measures (e.g. bioretention) could be applied to comply with these targets. As part of the stormwater quality management strategy for each site, rainwater tanks will also need to be installed to collect roof runoff from a minimum 75% of the roof area – with captured roofwater used to supplement non-potable water demands.
	DS21.1 Development achieves the air quality objectives set out in the Environmental Protection (Air) Policy 2008, as amended. DS21.2 Light emanating from any source complies with Australian Standard AS4282 Control of the Obtrusive Effects of Outdoor Lighting, as amended. DS21.3 Development does not include the storage of dangerous goods as defined by the Work Health and Safety Act 2011, as amended.
INFRASTRUCTURE	DS22.1 All development is connected to the reticulated water supply, sewerage, stormwater drainage and telecommunications infrastructure networks and has an electricity supply.

3.5.4 Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 2.8

Applications for Compliance Assessment to vary the lot layout in Sub-precinct 2.8 must be in accordance with the Plans and Design Standards outlined in this section.

Figure 9 identifies those fixed elements of the PoD that cannot be adversely impacted or changed. **Table 24** identifies the applicable Design Standards for a lot layout.




FIGURE 9 – SUB PRECINCT 2.8 FIXED ELEMENTS

TABLE 24 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.8

Design Standards	
Number of Local/Neighbourhood Parks	500m ² Town Square
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 9 .
Maximum Residential Yield (+/- 10%)	68 dwellings
Lot Design	No minimum lot size.
Block Sizes	For residential elements:- - Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres For non-residential elements:- - Length – 180m x 80m.

Design Standards	
	- Where block lengths exceed 120 metres, a mid-block pedestrian and cycle connection with a minimum width of 6 metres. - Parallel streets not more than 100 metres apart and total block perimeter no greater than 600 metres.
Lot Layout	- Lots intended for mixed use or multiple residential and lots with a width of 7.5 metres or less take up entire street block or are located on highly accessible block ends, corner lots and lots with dual road frontage. - Concentrations of lots with a width of 7.5 metres or less in an urban neighbourhood should be served by a rear lane.
Street Network	- Grid pattern or modified grid responsive to site characteristics. - Where slope allows, orientation within 15 degrees of north-south or east-west. - Connector and main streets of centres orientated to landmarks. - To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope.
Streets	- Street network includes a grid network of main streets, connector streets, access streets and lanes. - Street network promotes safe movements and provides direct pedestrian and cyclist access to the centre's focal point / transit opportunities. - Street network accommodates on-street parking and vehicle movements without compromising walking and cycling safety and amenity.
Typical Road and Cross Sections	Roads are designed generally in accordance with Appendix K .
PDA Guidelines	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) PDA Guideline No. 8 – Medium and High Rise Buildings (March 2014) PDA Guideline No. 9 – Centres (September 2013) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014)

3.6 Sub-Precinct 2.9 – Schools

3.6.1 Sub-Precinct Intent

This sub-precinct is intended to cater for the provision of two schools, co-located with a district sports park and a future community use site. This sub-precinct clusters these uses with the adjacent District Centre in Sub-precinct 2.8 to allow for easy access to community facilities.

An emerging community site (lot 80008) is also provided within this sub-precinct to cater for either:-

- a possible 5ha extension of a 4 ha (lot 80006) State High School Site; or
- residential dwellings delivered at a density consistent with that approved for the balance of the precinct under this Plan of Development.

The built form of the sub-precinct is low-medium rise. Building design positively contributes to the visual amenity of the sub-precinct, with built form addressing the street and promoting overlooking of the street to maximise casual surveillance.

Should lot 80008 be required for residential dwellings as opposed to school purposes a further application for Reconfiguration of a Lot will be required over that lot which will be subject to the compliance assessment process. Plans of Development consistent with those approved for the other predominantly residential sub-precincts shall accompany that application for compliance assessment, which upon approval will result in Home Based Business, House, Display Home and Multiple Residential (Duplex) as applicable being exempt development on the approved lots.

A community garden is proposed to provide places for learning and sharing about sustainable living practices for residents, visitors and school children.

3.6.2 Uses Subject to Compliance Assessment

The uses that comprise Approved Development subject to Compliance Assessment for Sub-precinct 2.9 are outlined in **Table 25** below.

TABLE 25 – USES FOR SUB-PRECINCT 2.9

Land Uses
Uses Subject to Compliance Assessment
On Lots 80003, 80005 and 80006
Community Facility Educational Establishment
On Lot 80008
Community Facility Display Home Educational Establishment Home Based Business House Multiple Residential (Duplex) Multiple Residential (other than duplex) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development. Other residential (retirement living only) and only where within a superlot approved in a change to Approved Reconfiguration a Lot Layout as permitted under this Plan of Development.
On Lot 80011
Community Facility

Land Uses
Place of Assembly
On Lot 90001
Outdoor Sport and Recreation (excluding a golf course)

3.6.3 Specific Design Criteria

Applications for Compliance Assessment in Sub-Precinct 2.9 are required to be assessed against and fulfil the Design Standards identified in **Table 26**.

TABLE 26 – DESIGN STANDARDS FOR SUB PRECINCT 2.9

Element	Design Standard
USE	DS1.1 Land uses comprise the uses specified for the sub-precinct in Table 25. DS1.2 In addition to the following Sub-precinct design standards, the use is in accordance with the relevant provisions of Section 3.9 Specific Use Criteria.
BUILT FORM	DS2.1 Development of the P – 6 (Prep to Grade 6) State School is generally in accordance with the approved PoD as contained within Appendix J. DS2.2 Development of the 7 – 12 (Grade 7 to Grade 12) State School is generally in accordance with the approved PoD as contained within Appendix J. DS3.1 For all non-residential development, building height does not exceed 5 storeys, except where buildings front a street with residential development, in which case building height does not exceed 3 storeys and 9 metres. DS4.1 Where a Required building frontage as shown on the approved PoD included in Appendix J, non-residential buildings:- (a) are to be a minimum of two (2) storeys; (b) shall be built to the boundary, where possible; (c) shall generally address the Main Street, where having frontage to the Main Street. DS4.2 Where a Desired building frontage as shown in the approved PoD included in Appendix J for the P – 6 (Prep to Grade 6) State School site, buildings are to be generally setback no more than 3 metres from the nominated Carparking – preferred location – School and Sports Fields. DS4.3 Where a nominated Landscape setback as shown on the approved PoD included in Appendix J, development is to incorporate landscaping that is generally 3 metres in width. DS4.4 Building entrances shall be located generally as shown in the approved PoD included in Appendix J DS4.5 Buildings shall be located generally in accordance with Indicative building footprints nominated on the approved PoD included in Appendix J.

Element	Design Standard
	DS4.6 Drop off zones are to be located generally in accordance with the approved PoD included in Appendix J .
PUBLIC REALM	DS5.1 Public realm should be provided with adequate lighting for safety. Care should be taken with lighting design to ensure that nearby residences are not affected by 'overspill'. DS5.2 The P – 6 (Prep to Grade 6) State School and the 7 – 12 (Grade 7 to Grade 12) State School are to be generally co-located with the 4ha Neighbourhood Sports Park as shown on the approved PoD included in Appendix J.
PARKING AND ACCESS	DS6.1 Site access points for vehicles are located generally as shown on the approved PoD, included in Appendix J. DS7.1 On site vehicle parking is provided at the rates outlined in Appendix H. DS7.2 Car parks shall be located generally in accordance with the locations nominated on the approved PoD included in Appendix J. DS7.2 On-site at-grade car parking areas are generally screened from view from surrounding streets by a combination of built form and planted buffers. DS8.1 Where possible, development provides for shared or multiple use of car parking areas, particularly large car parking areas:- (a) at times when car parking areas would otherwise not be occupied (e.g. weekends); and (b) when car parking spaces service two or more land uses with varying peak usage times (e.g. restaurants and entertainment uses which generate peak parking demands in periods when retail or office uses are relatively inactive). DS9.1 Bus Stops are provided generally as shown on the approved PoD, as contained within Appendix J.
ENVIRONMENT	DS10.1 Lighting emanating from any source complies with Australian Standard AS4282 Control of the Obtrusive Effects of Outdoor Lighting, as amended. DS10.2 Development of the land for a 7 – 12 (Grade 7 to Grade 12) State School is supported by a Stormwater Management Strategy demonstrating the achievement of standard best practice pollutant load removal targets. DS10.3 All rainwater tanks to residential dwellings are designed to ensure that 50% of rainwater is captured from the roof, to the purpose of supplying water to toilets, laundry, and have a connection for external usage. DS10.4 All rain tanks to residential dwellings are to be a minimum 5,000 litres capacity for detached houses and a minimum 3,000 litres capacity for semi-attached and attached houses DS10.5 All rainwater tanks to non-residential buildings are designed to ensure 75%

Element	Design Standard
	roof capture and reuse, with collected water used for all suitable applications within the property. DS10.6 For non residential sites, each site will need to demonstrate how they will satisfy standard best practice pollutant load removal targets (i.e. 80%, 60%, 45% and 90% removal of the average annual loads for total suspended solids, total phosphorus, total nitrogen, and gross pollutants). A range of stormwater quality management measures (e.g. bioretention) could be applied to comply with these targets. As part of the stormwater quality management strategy for each site, rainwater tanks will also need to be installed to collect roof runoff from a minimum 75% of the roof area – with captured roofwater used to supplement non-potable water demands.
INFRASTRUCTURE	DS11.1 All development is connected to the reticulated water supply, sewerage, stormwater drainage and telecommunications infrastructure networks and has an electricity supply.

3.6.4 Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 2.9

Applications for Compliance Assessment to vary the lot layout in Sub-precinct 2.9 must be in accordance with the Plans and Design Standards outlined in this section.

Figure 10 identifies those fixed elements of the PoD that cannot be adversely impacted or changed. **Table 27** identifies the applicable Design Standards for a lot layout.




FIGURE 10 – SUB PRECINCT 2.9 FIXED ELEMENTS

TABLE 27 – DESIGN STANDARDS FOR LOT VARIATIONS IN SUB PRECINCT 2.9

Design Standards for Lot 80008 if not required as an Educational Establishment	
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 7 .
Preferred Density	Consistent with that approved for the other predominantly residential sub-precincts within Precinct 2
Lot Design	Size - no minimum lot size Shape - Typical depth 20.0 - 40.0 metres, but can be less in urban neighbourhoods. Width in multiples of 2.5 metres and 5.0 metres consistent with typical lot dimensions - Urban lots are a typical depth of 13.5 – 15.0 metres Slope - Unless constructed in an integrated or attached development, the slope on a lot less than 450m² in area does not exceed: 10 per cent side slope 5 per cent lengthwise slope - Less, if both figures approach the maximum together. Platform construction required when finished slope on lot is 16 per cent or greater
Block Sizes	- Length 100-200 metres - Mid-block break providing a pedestrian link when blocks are over 130 metres - Depth 40-80 metres
Lot Layout	- No more than eight narrow (less than 10.0 metres) frontage lots in a row. - No more than six lots with a width of 7.5 metres to 5.0 metres in a row unless serviced by a rear lane. - No more than twelve lots with a width of less than 5.0 metres in a row. - Lot corners match or are within 1.0 metre of corners of adjoining lots. - Small lots are minimised at the end of T intersections and entrances to sub-precincts (if not serviced by rear lane).
Access	- Maximum 400 metres walk to neighbourhood recreation park or equivalent (see PDA Guideline No. 12 Park planning and design). - Clear, direct walk or cycle access to neighbourhood centre. - Ninety percent of all dwellings are within 400 metres of an existing or planned public transport stop
Street Network	- Grid pattern or modified grid responsive to site characteristics. - Where slope allows, orientation within 15 degrees of north-south or east-west. - Connector and main streets of centres orientated to landmarks. - To minimise cut & fill, streets follow ridges, gullies, and/or are perpendicular to slope. - Minimise cul-de-sacs and where used, limit length to desirably no greater than 10 lots.

Design Standards for Lot 80008 if not required as an Educational Establishment	
Streets	Street network includes: • A trunk connector providing access to neighbourhood connector streets; • Neighbourhood connector streets providing connections to neighbourhood destinations; • Neighbourhood access streets provide direct access to properties and neighbourhood lanes; and • Neighbourhood lanes – provide direct property access either at the front or rear of lots.
Typical Road Typologies and Cross Sections	Roads are designed generally in accordance with Appendix K .
Carparking	One room or one bedroom house • 0.5 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit. Two or more bedroom house • 0.75 on-street parking space per house/dwelling unit is provided within reasonable proximity of the house/dwelling unit A parking analysis plan in accordance with the PDA Practice Note – Parking Analysis Plan is required to demonstrate compliance with the above standards if the development proposal includes lots less than 12.5m wide, and/or a Multiple residential development including up to 6 dwelling units. Relaxation to the above standards may be approved where: • The development is in proximity to high frequency public transport (e.g. within 800metres of a railway station) and/or • The development secures a higher proportion of on-site parking
PDA Guidelines and Practice notes	PDA Guideline No. 5 – Neighbourhood Planning and Design (March 2014) ULDA Guideline No. 6 – Street and Movement Network (April 2012) ULDA Guideline No. 12 – Park Planning and Design (November 2011) PDA Guideline No. 13 – Engineering Standards (March 2014) PDA Guideline No. 18 – Development Interfaces (March 2014) PDA Practice Note No. 7 – Designing for Small Lots (March 2014) PDA Practice Note No. 10 – Plans of Development (March 2014) PDA Practice Note No. 11 - Parking Analysis Plans (July 2012) PDA Practice Note No. 12 – Rear Lanes: Design and Development (March 2014)
Design Standards for the overall Sub-precinct	
Lifestyle Buffer	A 'Lifestyle Buffer' is provided generally in accordance with Figure 7 .
Boundary	Variations to the configuration of the non-residential lots are permitted where

Design Standards for Lot 80008 if not required as an Educational Establishment	
Rearrangement	detailed design of the uses to occur on the lots dictates a revised configuration. It is to be noted however that the general arrangement detailed in Figure 10 is intended to provide primary guidance for any changes.

3.7 Sub-Precinct 6.1 – Eco Sanctuary

3.7.1 Sub-Precinct Intent

This Sub-Precinct comprises part of the Environmental Protection Zone required by the Development Scheme and is intended to be protected for conservation and rehabilitation purposes with opportunities for recreation and limited opportunities for the provision of infrastructure and water quality and quantity management where appropriate.

The sub-precinct includes areas, including a stand of significant Blackbutt forest, that are of environmental significance and have associated conservation, biodiversity, habitat or scenic amenity values. The sub-precinct accommodates elements for an integrated open space network that respond to community needs provided they do not compromise environmental values.

Development in this area is to predominantly comprise passive and active recreational opportunities, inclusive of an integrated tourist attraction. The built form within this Sub-precinct is minimal and is to be subordinate to the primary use of the area for recreational uses. A community garden is encouraged within sub-precinct 6.1 to provide places for learning and sharing about sustainable living practices for residents.

A range of low scale facilities are anticipated as being established within this sub-precinct as part of an *Integrated Tourist Attraction*, which is intended to promote environmental awareness, education and conservation and the carrying out of sustainable practices.

Pedestrian access to and through this sub-precinct is encouraged from all edges of the precinct. Vehicular access is to be limited to key access points only.

3.7.2 Uses Subject to Compliance Assessment

The uses that comprise Approved Development subject to Compliance Assessment for sub-precinct 6.1 are outlined in **Table 28** below.

TABLE 28 – USES FOR SUB-PRECINCT 6.1

Land Uses	
Uses Subject to Compliance Assessment	
Community Facility	Integrated Tourist Attraction
Indoor Sport and recreation	Utility Installation
Outdoor Sport and Recreation (excluding a golf course)	

3.7.3 Specific Design Criteria

Applications for Compliance Assessment in Sub-Precinct 6.1 are required to be assessed against and fulfil the Design Standards identified in **Table 29**.

TABLE 29 – DESIGN STANDARDS FOR SUB PRECINCT 6.1

Element	Design Standard
USE	DS1.1 Land uses comprise the uses specified for the sub-precinct in Table 28. DS1.2 In addition to the following Sub-precinct design standards, the use is in accordance with the relevant provisions of Section 3.9 Specific Use Criteria.
BUILT FORM	DS2.1 Development of the sub-precinct is generally in accordance with the approved PoD as contained within Appendix L. DS2.2 The design of the Integrated Tourist Facility is to ensure that it is integrated with the adjoining Major Recreation Park and that a high degree of pedestrian permeability between the two sites is achieved. DS3.1 For all development, building height does not exceed 11 metres and 3 storeys, with the exception of Landmark structures (e.g. wind turbine or sculpture / spire) which may extend to 15 metres in height. DS4.1 The size, scale and density of the <i>Integrated Tourist Attraction</i> is to accord with the following:- (a) a maximum gross floor area of 1,500m² (excluding associated accommodation); and (b) a maximum of 30 accommodation units, which shall be ancillary to the primary use of the premises for an environmental and sustainable education centre. DS5.1 Built form setbacks are generally in accordance with the following:- (a) For the Community Facility site as contained within the approved RoL plans at Appendix B any building is:- (i) setback a minimum of 3 metres from all site boundaries; and (ii) is to be designed to ensure that it complements the adjoining Integrated Tourist Facility, through building materials, colours and overall design that is generally complementary to the built form; (b) For development in the sub-precinct other than identified in (a) above, any building is setback a minimum of:- (i) 20 metres from all site boundaries adjoining a residential use, (ii) 3 metres from all site boundaries where (i) above does not apply. DS6.1 Sub-tropical design elements are incorporated within building design, including but not limited to: (a) the maximising of natural light and cross-ventilation; (b) the provision of fixed and adjustable sun shading devices to control direct solar access; and (c) the provision of roof eave overhangs to walls, wall openings and balconies. DS6.2 The scale, design and external finish of buildings:- (a) complements the natural character of the area and integrates with the surrounding natural landscape; and (b) incorporates colours and finishes that allow the buildings to blend in with the

Element	Design Standard
	natural landscape. DS6.3 Buildings that take the form of small, separate buildings which are visually separated. The architectural style and materials used for any new building:- (a) comprise a mix of lightweight and textured external materials such as timber cladding and corrugated iron roofs; (b) reflect the line, form, colour and texture found in the existing landscape and do not replicated artificial or imported themes; and (c) use muted earth/environmental tones that blend with the natural environment. DS6.4 Low reflectivity roofing and building materials are used. DS7.1 Where a Desired building frontage as shown on the approved PoD included in Appendix L, buildings are to address the adjacent road frontage. DS7.2 Where a nominated Required landscape edge as shown on the approved PoD included in Appendix L, development is to incorporate landscaping that is generally 3 metres in width. DS7.3 Building entrances shall be located generally as shown on the approved PoD included in Appendix L. DS7.4 Buildings shall be located generally in accordance with Indicative building footprints nominated on the approved PoD included in Appendix L. DS8.1 Any accommodation provided as part of an <i>Integrated Tourist Attraction</i> is provided for short term stays only, with guests staying no more than 14 consecutive nights.
PUBLIC REALM	DS9.1 Public realm should be provided with adequate lighting for safety. Care should be taken with lighting design to ensure that nearby residences are not affected by 'overspill'. DS9.2 Development of an <i>Integrated Tourist Attraction</i> incorporates site landscapes that:- (a) provide an attractive landscape setting for the enjoyment and appreciation of visitors; (b) visually screen and soften built form elements and integrated the development into the surrounding landscape; (c) utilise native endemic vegetation as the major planting theme; and (d) maximise the retention of existing mature trees in order to retain the landscape character of the area.
PARKING AND ACCESS	DS10.1 Vehicle access points for vehicles are located generally as shown on the approved PoD, included in Appendix L. DS10.2 On site vehicle parking is provided at the rates outlined in Appendix H. DS10.3 Car parks shall be located generally in accordance with the locations nominated on the approved PoD included in Appendix L. DS10.4 On-site at-grade car parking areas are generally screened from view from surrounding streets by planted buffers.

Element	Design Standard
	DS10.5 Where possible, development provides for shared or multiple use of car parking areas, particularly large car parking areas:- (a) at times when car parking areas would otherwise not be occupied (e.g. weekends); and (b) when car parking spaces service two or more land uses with varying peak usage times.
ENVIRONMENT	DS11.1 Development achieves the noise generation levels set out in the Environmental Protection (Noise) Policy 2008, as amended DS11.2 Development achieves the air quality objectives set out in the Environmental Protection (Air) Policy 2008, as amended. DS11.3 Light emanating from any source complies with Australian Standard AS4282 Control of the Obtrusive Effects of Outdoor Lighting, as amended. DS11.4 Development does not include the storage of dangerous goods as defined by the Work Health and Safety Act 2011, as amended. DS11.5 All rainwater tanks to non-residential buildings are designed to ensure 75% roof capture and reuse, with collected water used for all suitable applications within the property. DS11.6 For non residential sites, each site will need to demonstrate how they will satisfy standard best practice pollutant load removal targets (i.e. 80%, 60%, 45% and 90% removal of the average annual loads for total suspended solids, total phosphorus, total nitrogen, and gross pollutants). A range of stormwater quality management measures (e.g. bioretention) could be applied to comply with these targets. As part of the stormwater quality management strategy for each site, rainwater tanks will also need to be installed to collect roof runoff from a minimum 75% of the roof area – with captured roofwater used to supplement non-potable water demands.
INFRASTRUCTURE	DS12.1 All Development is connected to the reticulated water supply, sewerage, stormwater drainage and telecommunications infrastructure networks and has an electricity supply with the exception of Lot 80010 being the Eco Centre Lot. The intent of the Eco Centre (Lot 80010) is to be developed as an 'off the grid' integrated tourist attraction. As such, the Eco Centre retains the ability to be developed with its own on-site waste water system rather than be required to connect to the reticulated sewerage infrastructure.

3.7.4 Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 6.1

Variation to the lot layout within Sub-Precinct 6.1 is not intended.

3.8 Sub-Precinct 6.2 – Conservation

3.8.1 Sub-Precinct Intent

This sub-precinct comprises part of the Environmental Protection Zone required by the Development Scheme and part of the Conservation Buffer (that comprises the Riparian Corridor, Frog Zone and Frog Buffer associated with Lamerough Creek and Bells Creek North) and is to be extensively rehabilitated as an environmental protection and habitat area. It is intended that this sub-precinct be protected for conservation

and rehabilitation purposes. The sub-precinct may accommodate elements for an integrated open space network providing for multipurpose functions that respond to community needs provided they do not compromise environmental values.

3.8.2 Uses Subject to Compliance Assessment

The uses that comprise Approved Development subject to Compliance Assessment for sub-precinct 6.2 are outlined in **Table 30** below.

TABLE 30 – USES FOR SUB-PRECINCT 6.2

Land Uses
Uses Subject to Compliance Assessment
Nil

3.8.3 Criteria for a Change to Approved Reconfiguring a Lot Layout for Sub-Precinct 6.2

Variation to the lot layout within Sub-precinct 6.2 is not intended.

3.9 Specific Use Criteria

In addition to the detailed provisions for each sub-precinct, specific use provisions specified in **Table 31** are applicable to Approved Development subject to the Compliance Assessment process under **Section 1.5.2** of the PoD. These provisions are only applicable as relevant to the specific use being assessed.

TABLE 31 – SPECIFIC USE DESIGN STANDARDS

Use	Design Standards
Child Care Centre	DS1.1 Child care centres are located generally where shown on the approved PoD, included in Appendix I. OR DS1.2 Child care centres are to be located with frontage to a Main street or Trunk Connector.
	DS2.1 Child care centres are to be located on a site having:- (a) A slope of not more than 10%; (b) A regular shape (or suitable to accommodate the use) ; and (c) A minimum area of 1,500m²
	DS3.1 All buildings, structures and outdoor play areas are set back at least 3 metres from all site boundaries adjoining a residential use (or future residential use).
	DS4.1 A minimum 1.8 metre high solid acoustic screen fence is erected along the full length of all site boundaries adjoining a residential use (or future residential use).
Community Facility	DS5.1 Community facilities are located and designed generally in accordance with the approved PoDs included in Appendix I and Appendix L. OR DS5.2 Community facilities are located adjacent to the District Centre, Educational establishment (primary or secondary school) or land used for a Park or Outdoor Sport and Recreation. DS5.3 A maximum 1 hectare area of serviced land for District Community facilities including a multi purpose performance facility, community meeting space and youth space is to be located within Sub-precinct 2.8. This may be provided as two separate lots (in Precincts 2.8 and 2.9) totalling 1 hectare. DS5.4 A maximum 4,000m² area of serviced land incorporating a neighbourhood meeting room is to be located within Sub-precinct 6.1. DS5.5 Where adjoining a residential use, a minimum 1.8 metre high solid acoustic screen fence is provided along the full length of all common site boundaries. DS5.6 Intrusive outdoor activities are located and orientated away from residential premises.

Use	Design Standards
Educational Establishment	DS6.1 A 9 hectare area of land for a 7 – 12 (Grade 7 to Grade 12) State School is provided within Sub-precinct 2.9, as shown on the approved RoL Plan, included in Appendix B. DS6.2 A 4 hectare area of land for a P – 6 (Prep to Grade 6) State School is provided within Sub-precinct 2.9, as shown on the approved RoL Plan, included in Appendix B. DS6.3 The P – 6 (Prep to Grade 6) State School and the 7 – 12 (Grade 7 to Grade 12) State School are to be co-located with the 4ha District Sports Park as shown on the approved PoD included in Appendix J. DS6.4 The P – 6 (Prep to Grade 6) State School is to be designed generally in accordance with the approved PoD included in Appendix J. DS6.5 The 7 – 12 (Grade 7 to Grade 12) State School is to be designed generally in accordance with the approved PoD included in Appendix J.
Emergency Services	DS7.1 Emergency Services are located to enable easy access to a Sub-arterial or Connector Road. DS7.2 Where adjoining a residential use, a minimum 1.8 metre high solid acoustic screen fence and a 2 metre wide landscape strip is provided along the full length of all common site boundaries.
Fast Food Premises	DS8.1 Fast Food premises are not to immediately adjoin a residential (or future Residential) use.
	DS9.1 Loading areas are not able to be viewed from the road or any public space
Indoor Entertainment (Tavern / Hotel)	S10.1 Indoor Entertainment (Tavern / Hotel) uses are located as shown on the PoD included in Appendix I .
Indoor Sport and Recreation	DS11.1 Indoor Sport and Recreation uses exclude premises for conducting large scale functions, i.e. convention centre, amusement and leisure centre; and DS11.2 Indoor Sport and Recreation uses have a maximum GFA of 2,000m².
Market	DS12.1 Where market stalls are proposed to be located adjacent to existing shops the market is not held on more than 1 day per week.
	DS13.1 Pedestrian access or pathways, a minimum of 2 metres wide, are provided between:- (a) stall fronts; and (b) stalls and existing shop fronts. DS13.2 Public toilets:- (a) are provided within the area of the market, or are located within 250 metres of the market; and

Use	Design Standards
	(b) remain open and accessible for use during market hours. DS13.3 Directional signage is provided to identify the location of, and entry to, public toilet facilities.
	DS14.1 The market is conducted, including setup and pack-up time, between the hours of 6.00am and 10.00pm. DS14.2 Noise generated from the market complies with the level of noise emissions prescribed under the Environmental Protection (Noise) Regulations 1997. DS14.3 Any outdoor lighting associated with the market is designed, installed, operated and maintained in accordance with AS4282 – The Control of the Obtrusive Effects of Outdoor Lighting. DS14.4 Any temporary lighting is dismantled immediately on closure of the market.
	DS15.1 The area used for market purposes is maintained in a clean, safe and tidy state:- (a) during market hours; and (b) at the conclusion of each day's trading.
	DS16.1 A clear movement path, at least 3 metres in width, is maintained through or around the market to allow emergency vehicle access.
Multiple Residential (other than duplex)	DS17.1 For Multiple Residential uses involving more than two units, density is to be a minimum of 35 dwellings/ha, calculated over the site on which it is located.
	DS18.1 For all Multiple Residential uses involving more than two units, the building is sited and designed such that:- (a) the main pedestrian entrance to the building (or group of buildings) is located on the primary street frontage; (b) access from the street to the entrance of the building(s) or individual dwellings is easily discerned; (c) vehicular access to the site is separate from the pedestrian access; (d) street and parkland frontages comprise “semi-active uses/spaces” such as habitable rooms of dwellings or rooming units, common recreation areas (indoor and outdoor) and landscaped areas, to facilitate casual surveillance; (e) the number of dwellings, windows and balconies of habitable rooms that address adjoining streets, communal recreation areas and open spaces is optimised.
	DS19.1 Non habitable rooms of one dwelling are not located opposite windows of another dwelling unless views are controlled by screening devices, distance, landscaping or design of the opening. DS19.2 Where habitable room windows look directly at habitable room windows in an adjacent dwelling within 2 metres at the ground storey, or 9 metres at levels above the ground storey, privacy is protected by:-

Use	Design Standards
	(a) window heights being a minimum of 1.5 metres above floor level; or (b) fixed translucent glazing being applied to any part of a window below 1.5 metres above floor level; or (c) fixed external screens; or (d) if at ground level, screen fencing to a minimum height of 1.8 metres.
	DS20.1 The length of any unarticulated elevation of a building, fence or other structure visible from the street does not exceed 15 metres.
	DS21.1 Any car parking area or other associated structures are integrated into the design of the development such that:- (a) they are screened from view from frontages to streets, parks and adjoining land; (b) they are not located between the building and the street address; and (c) a basement or undercroft car parking area does not protrude above the adjacent ground level by more than 1 metre. DS21.2 Services and mechanical plant, including individual air conditioning equipment for dwellings or rooming units, is visually integrated into the design and finish of the building or effectively screened from view.
	DS22.1 The site cover of Multiple Residential buildings does not exceed: (a) 60% if within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7; (b) 80% within Sub-precinct 2.8. DS22.2 Building setbacks comply with those shown for the relevant allotment width as included in Appendix F unless otherwise specified in any applicable Sub-precinct specific Plan of Development.
	DS23.1 Except where specified otherwise in a Sub-precinct specific Plan of Development: (a) A 2 metre wide landscaped buffer strip is provided along the full frontage of the site; (b) At least 10% of the site area is provided as communal open space exclusive of required buffer strips and clothes drying areas; (c) A minimum 1.8 metre high solid screen fence is provided and maintained along the full length of any side or rear boundary; DS23.2 For all Multiple Residential uses involving more than two units:- (a) Each ground floor dwelling has a courtyard or similar private open space of not less than 15m² with a minimum dimension of 3 metres directly accessible from the main living area; (b) Each dwelling above ground level has a balcony or similar private open space area of not less than 9m² with a minimum dimension of 3 metres directly accessible from the living area of the dwelling or rooming unit.

Use	Design Standards
	DS24.1 For Multiple Residential uses within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7, front fences and walls:- (a) have a maximum height of not more than:- (i) 1.8 metres if 50% transparent; or (ii) 1.2 metres if solid. (b) are setback behind the 2 metre wide landscape strip. DS25.1 Building bulk is reduced by incorporating a combination of the following elements in building design:- (a) variations in plan shape, such as curves, steps, recesses, projections or splays; (b) variations in vertical profile, with steps or slopes at different levels; (c) variations in the treatment and patterning of windows, sun protection and shading devices, or other elements of a façade treatment at a finer scale than the overall building structure; (d) balconies, verandahs or terraces; and (e) planting, particularly on podiums, terraces and low level roof decks. DS26.1 Within Sub-precinct 2.8:- (a) entry areas for the residents and visitors are provided separately from entrances for other building users and provide for safe entry from streets, car parking areas and servicing areas; (b) clearly marked, safe and secure parking areas are provided for residents and visitors which is separate from parking areas provided for other building users; (c) security measures are installed such that building users do not have access to areas that are intended for the exclusive use of residents and visitors.
Other Residential (retirement living)	DS27.1 The use is located within 400m walking distance of a public transport stop which provides direct access to a District Centre or Town Centre. DS28.1 Except where otherwise specified in an approved PoD, the site cover of the buildings does not exceed 50%. DS28.2 Building bulk is reduced by incorporating a combination of the following elements in building design:- (a) verandahs; (b) recesses; (c) variation in materials, colours and / or textures including between levels; and (d) variation in building form. DS28.3 The length of any unarticulated elevation of a building, fence or other structure visible from the street does not exceed 15 metres. DS28.4 Any building does not exceed 40 metres in length, with separation between buildings, for the purposes of cross ventilation, articulation and light, of at least 6 metres. DS29.1 Buildings are oriented to the street and provide casual surveillance of the street. DS29.2 Buildings setbacks comply with those shown for the relevant allotment

Use	Design Standards
	width as included in Appendix F. DS29.3 Screening of balconies is limited to the side and rear of boundaries, and the sides of balconies where needed, to prevent noise and overlooking of other dwellings and recreation areas. DS29.4 Any car parking area or other associated structures are integrated into the design of the development such that they are screened from view from frontages to streets, parks and adjoining land. DS29.5 Services structures and mechanical plant are screened or designed as part of the building.
	DS30.1 Dwellings are configured in clusters with each cluster having a clearly defined street address or access corridor and each dwelling having clearly defined private open space and a prominent front door. DS30.2 Clusters of dwellings are supported by unique design features that help identify and individualise them and assists residents and visitors to easily find their way. DS30.3 Logical, direct and separated pedestrian and vehicle routes are provided between dwellings, communal buildings and other on-site facilities and facilities in the neighbourhood.
	DS31.1 At least 10% of the area of the site is provided as communal and private open space, with:- (a) each ground floor dwelling having a courtyard or similar private open space area, not less than 15m² and with a minimum dimension of 3 metres, directly accessible from the living area of the dwelling; (b) each dwelling above ground level having a balcony or similar private open space area, not less than 9m² and with a minimum dimension of 2.5 metres, directly accessible from the living area of the dwelling. DS31.2 A landscape strip at least 2 metres wide is provided within the boundaries of the site, adjacent to the full frontage of the site.
	DS32.1 A 1.8 metre high solid screen fence is provided along the full length of all side and rear boundaries of the site. DS32.2 Unless required to ameliorate traffic noise or headlight glare, high solid fences or walls are avoided along street frontages. DS32.3 Front fences and walls:- (a) have a maximum height of not more than:- (i) 1.8 metres if 50% transparent; or (ii) 1.2 metres if solid. (b) are setback behind the 2 metre wide landscape strip.
	DS33.1 The development provides management facilities, supervised care facilities and social and recreational facilities in the form of:- (a) a live-in manager's residence and office;

Use	Design Standards
	(b) 24 hour nursing station and / or 24 hour monitored alert system; (c) communal dining room; (d) communal indoor social/recreation space; and (e) a diversity of informal indoor and outdoor social spaces. DS33.2 Communal buildings are easily accessible and centrally located, and resident are able to easily navigate the site on foot or with the assistance of mobility aids. DS34.1 No dwelling is more than 250 metres walking distance from a site entry or exit point, or any central community facilities building. DS34.2 All pathways and land use for outdoor recreation have grades of 5% or less, with paths having hard, slip resistant surfaces. DS34.3 Internal paths, ramps and hallways are capable of accommodating two wheelchairs (side by side) at any one time. DS34.4 Buildings exceeding one storey in height incorporate lifts to each level. DS35.1 The development has access to a reliable alternative power supply in the event of prolonged power outage or disconnection from grid supplied electricity. DS35.1 A Site Evacuation Plan with practical and reliable arrangements for the evacuation of all persons on-site to the nearest activity centre is prepared.
Outdoor Sport and Recreation (excluding Golf Course)	DS36.1 The use is located in accordance with the approved Landscape Master Plan. DS36.2 The use is located and designed so as to be:- (a) convenient to users; and (b) compatible with the preferred character of the local area. DS36.3 The use:- (a) is effectively designed to meet the needs of users, having regard to the scale and nature of the use; (b) has buildings and structures that are fit for purpose; and (c) has buildings and structures that incorporate passive design responses that acknowledge and reflect the region's sub-tropical climate. DS36.4 Mechanical plant and equipment and storage areas associated with the use are designed and screened so as to provide an attractive address to streets and adjoining properties. DS36.5 Any structure associated with the use does not result in a significant loss of amenity for surrounding development, having regard to:- (a) the extent and duration of lighting and overshadowing; (b) privacy and overlooking impacts; (c) impacts on views and vistas; and (d) the scale of the structure relative to its surroundings. DS36.6 A temporary drive in theatre:

Use	Design Standards
	(a) is limited to occasional use up to a maximum of 12 times per year, and (b) is to be operated in association with the adjoining Display Village, and (c) can occur only for as long as the Display Village is in operation, and (d) must ensure that light spill, noise, litter, traffic and car parking impacts does not adversely impact upon the amenity of any adjoining or nearby premises.
Shop, Business and Food Premises	DS44.1 Shops, Businesses and Food Premises within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7 are to be located generally as shown on the approved PoD plan/s as contained within Appendix E and are to meet the following: (a) are located on a corner lot where at least one of the intersection roads is a Connector Road; (b) are no more than 250m² GFA; (c) do not to exceed a maximum building height of 11 metres and 3 storeys; (d) do not extend an existing centre, approved Shop, Business or Food Premises.
	DS45.1 Buildings setbacks for Shops, Businesses and Food Premises within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7 comply with those shown for the relevant allotment width as included in Appendix F.
	DS46.1 Where a building exceeds 2 storeys in height, the building is designed so as to avoid the creation of adverse micro-climatic impacts on any nearby public space by way of overshadowing, wind tunnelling or reflective glare. DS46.2 Building materials and hard surfaces used in landscape works are not highly reflective, or likely to create glare, slippery or otherwise hazardous conditions. DS46.3 Any outdoor public or semi-public open space has a minimum of 50% of its area covered or shaded. DS46.4 Development provides for a minimum of 65% of the building frontage to a public street, or other public or semi-public space, to present with clear or relatively clear windows and glazed doors.
	DS47.1 The site cover of a Shop, Business or Food Premises within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7 does not exceed:- (a) 70% for that part of a building up to 2 storeys in height; and (b) 50% for that part of a building exceeding 2 storeys in height.
	DS48.1 The building has articulated and textured facades that incorporate some or all of the following design features to create a high level of openness and visual interest, and provide shading to walls and windows:- (a) wide colonnades, verandahs, awnings, balconies and eaves; (b) recesses, screens and shutters; and (c) windows that are protected from excessive direct sunlight during warmer months. DS48.2 To assist in creating or maintaining a coherent streetscape, the building is articulated and finished in ways that respond to attractive and notable elements of adjacent buildings, such as continuity of colonnades, verandahs, balconies, eaves,

Use	Design Standards
	parapet lines and roof forms. DS48.3 The building incorporates vertical and horizontal articulation such that no blank wall is longer than 15 metres. DS49.1 A building having a height of more than 2 storeys incorporates variations in materials, colours, textures or other built form elements that help to differential between the podium and other building levels. DS50.1 For a Shop, Business or Food Premises within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7 a minimum of 10% of the site is comprised of deep planted landscapes. DS50.2 Landscapes are provided on-site in accordance with the following:- (a) shade trees, low planting and hard landscapes are provided along street frontages not occupied by buildings or driveways; (b) shade trees are provided in car parks; (c) a landscape strip is provided between the business use and any adjacent residential use which:- (i) is planted with a variety of screening trees and shrubs; and (ii) incorporates a minimum 1.8 metre high solid screen fence where acoustic attenuation is required; and (d) planting is provided on top of podium levels. DS51.1 Undesirable visual, noise and odour impacts on public spaces and residential uses are avoided or minimised by:- (a) where appropriate, limiting the hours of operation of the business use to maintain acceptable levels of residential amenity relative to the site's context and setting; (b) providing vehicle loading / unloading and refuse storage / collection facilities within enclosed serviced yards or courtyards; (c) locating site service facilities and areas such that they are not adjacent to the frontage of a street or public space. DS51.2 Glare conditions or excessive 'light spill' on to adjacent sites and public spaces are avoided or minimised through measures such as:- (a) careful selection and location of light fixtures; (b) use of building design / architectural elements or landscape treatments to block ore reduce excessive light spill to locations where it would cause a nuisance to residents or the general public; and (c) alignment of streets, driveways and servicing areas to minimise vehicle headlight impacts on adjacent residential accommodation.
Short Term Accommodation	DS52.1 For Short Term Accommodation involving more than two units, density is to be a minimum of 35 dwellings/ha, calculated over the site on which it is located. DS53.1 For all Short Term Accommodation uses involving more than two units, the building is sited and designed such that:- (a) the main pedestrian entrance to the building (or group of buildings) is located on the primary street frontage;

Use	Design Standards
	(b) access from the street to the entrance of the building(s) or individual dwellings is easily discerned; (c) vehicular access to the site is separate from the pedestrian access; (d) street and parkland frontages comprise “semi-active uses/spaces” such as habitable rooms of dwellings or rooming units, common recreation areas (indoor and outdoor) and landscaped areas, to facilitate casual surveillance; (e) the number of dwellings, rooming units, windows and balconies of habitable rooms that address adjoining streets, communal recreation areas and open spaces is optimised.
	DS54.1 Non-habitable room windows of one rooming unit is not located opposite windows of another dwelling or rooming unit unless views are controlled by screening devices, distance, landscaping or design of the opening. DS54.2 Where habitable room windows look directly at habitable room windows in an adjacent rooming unit within 2 metres at the ground storey, or 9 metres at levels above the ground storey, privacy is protected by:- (a) window will heights being a minimum of 1.5 metres above floor level; or (b) fixed translucent glazing being applied to any part of a window below 1.5 metres above floor level; or (c) fixed external screens; or (d) if at ground level, screen fencing to a minimum height of 1.8 metres.
	DS55.1 The length of any unarticulated elevation of a building, fence or other structure visible from the street does not exceed 15 metres.
	DS56.1 Any car parking area or other associated structures are integrated into the design of the development such that:- (a) they are screened from view from frontages to streets, parks and adjoining land; (b) they are not located between the building and the street address; and (c) a basement or undercroft car parking area does not protrude above the adjacent ground level by more than 1 metre. DS56.2 Services and mechanical plant, including individual air conditioning equipment for dwellings or rooming units, is visually integrated into the design and finish of the building or effectively screened from view.
	DS57.1 The site cover of Short Term Accommodation buildings does not exceed: (a) 60% if within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7; (b) 80% within Sub-precinct 2.8 and 6.1. DS57.2 Building setbacks comply with those shown for the relevant allotment width as included in Appendix F except where specified otherwise in a Sub-precinct specific Plan of Development.
	DS58.1 Except where specified otherwise in a Sub-precinct specific Plan of Development: (a) A 2 metre wide landscaped buffer strip is provided along the full frontage of the site;

Use	Design Standards
	(b) At least 10% of the site area is provided as communal open space exclusive of required buffer strips and clothes drying areas; (c) A minimum 1.8 metre high solid screen fence is provided and maintained along the full length of any side or rear boundary; DS58.2 For all Short Term Accommodation involving more than two units:- (a) Each ground floor rooming unit has a courtyard or similar private open space of not less than 15m² with a minimum dimension of 3 metres directly accessible from the main living area; (b) Each rooming unit above ground level has a balcony or similar private open space area of not less than 9m² with a minimum dimension of 3 metres directly accessible from the living area of the dwelling or rooming unit. DS59.1 For Short Term Accommodation within Sub-precincts 2.1, 2.2, 2.3, 2.4, 2.5, 2.6 and 2.7, front fences and walls:- (a) have a maximum height of not more than:- (i) 1.8 metres if 50% transparent; or (ii) 1.2 metres if solid. (b) are setback behind the 2 metre wide landscape strip. DS59.1 Building bulk is reduced by incorporating a combination of the following elements in building design:- (a) variations in plan shape, such as curves, steps, recesses, projections or splays; (b) variations in vertical profile, with steps or slopes at different levels; (c) variations in the treatment and patterning of windows, sun protection and shading devices, or other elements of a façade treatment at a finer scale than the overall building structure; (d) balconies, verandahs or terraces; and (e) planting, particularly on podiums, terraces and low level roof decks. DS60.1 Within Sub-precincts 2.8 and 6.1:- (a) entry areas for the residents and visitors are provided separately from entrances for other building users and provide for safe entry from streets, car parking areas and servicing areas; (b) clearly marked, safe and secure parking areas are provided for residents and visitors which is separate from parking areas provided for other building users; (c) security measures are installed such that building users do not have access to areas that are intended for the exclusive use of residents and visitors. DS61.1 Except where in the form of a serviced apartment or self-contained accommodation, the rooming accommodation or short term accommodation use is provided with sufficient kitchen, dining, laundry and common room facilities to accommodate the needs of residents and staff.
Telecommunications Facility	DS62.1 For Telecommunications facilities that are to be located on an existing or proposed building, these are to be integrated within the building and are not to adjoin a residential use.

Appendix A

Definitions

Integrated Tourist Attraction: *Means the use of premises for providing on site entertainment, recreation or similar facilities for the general public. It includes the use of land or premises intended for the conservation, interpretation and appreciation of areas of environmental, cultural or heritage value, local ecosystems and attributes of the natural environment. Activities typically:-*

- *maintain a nature based focus or product;*
- *promote environmental awareness, education and conservation;*
- *carry out sustainable practices.*

Facilities may include a tourist facility based around sustainability display and an environmental education centre, wetland, conference centre and associated accommodation, car parking and a community based nursery / market garden centre.

Lifestyle Buffer

Means a buffer with a minimum width of 30m from the boundary of each Frog Buffer. This buffer provides for separation between development areas and residential (building) areas. Refer to the latest approved Acid Frog Management Plan for additional detail.

Stockland

Means Stockland Corporation Limited and any subsidiary company.

Appendix B

Approved Reconfiguring a Lot Plans:

Ref I67I00-112 Rev AD,

I67I00-114 Rev AD,

I67I00-116 Rev AD,

I67I00-118 Rev AD,

I67I00-120 Rev AD,

I67I00-122 Rev AD,

I67I00-124 Rev AD,

I67I00-126 Rev AD,

I67I00-137 Rev AD and

Development Statistics Plan Ref I67I00-113 Rev AD

RPS

Appendix C

Overall Staging Plan Ref I67I00-110 Rev AD

RPS

Appendix D

Signage Plan of Development Ref I67I00-2I-I07_2Z
RPS

Appendix E

Approved Plans of Development

Ref I67I00-115 Rev AD,

I67I00-117 Rev AD,

I67I00-119 Rev AD,

I67I00-121 Rev AD,

I67I00-123 Rev AD,

I67I00-125 Rev ADD,

I67I00-21-107_1Z(Plan of Development – Sub-Precincts)

I67I00-21-107_3Z (Small Non Residential Nodes and Business)
and

I67I00-21-107_5AA (Connectivity)

RPS

Appendix F

Standard Allotment Diagrams Ref I67I00-47Z Sheet I of I5 to
Sheet I5 of I5

RPS

Appendix G

Location of Freestanding Telecommunications Facilities Ref
I67I00-2I-I07_4Z and

PMT (Transformer) Sites Ref I67I00-2I-I07_7Z

RPS

Appendix H

Car Parking Rates

Land Use	Car spaces	Service vehicle spaces	Cycle spaces
Business²	1 space / 30m ² GFA OR 1 space / 40m ² GFA where in Sub-Precinct 2.8.	- Where $\leq 200\text{m}^2$ GFA – SRV - Where 201m² to 600m² GFA – VAN + MRV - Where $\geq 600\text{m}^2$ GFA – 1 VAN + 1 SRV + 1 MRV	1 employee space / 190m ² GFA + 1 customer space / 700m ² GFA
Child Care Centre	1 employee space / employee + 1 customer space / 7 children	VAN	1 employee space / 100m ² GFA
Educational Establishment	Sufficient spaces to accommodate the number of vehicles likely to be parked at any one time	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time (with min. 1 WCV bay)	1 student / employee space / 100m ² GFA
Emergency Services	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time
Utility Installation			
Sales Office	2 spaces	Not required	Not required
Food Premises¹	1 space / 20m ² GFA where in Sub-Precinct 2.8 OR 1 space / 15m ² GFA where in all other Sub-Precinct/s.	- Where $\leq 200\text{m}^2$ GFA – SRV - Where 201m² to 600m² GFA – VAN + MRV - Where $\geq 600\text{m}^2$ GFA – 1 VAN + 1 SRV + 1 MRV	1 employee space / 190m ² GFA + 3 customer spaces
Fast Food Premises¹			
Indoor Entertainment (Tavern)¹			
Place of Assembly	1 space / 15m ² GFA	- Where requiring access via a road – SRV (Type A Access) + occasional access for MRV - Where requiring access via a street – SRV (Type B Access) + occasional access for MRV	1 space / 50m ² GFA
Community Facility	1 space / 20m ² GFA	VAN + WCV (where	1 employee space / 50m ²

² (a) Where gross floor area exceeds 200m², provision is to be made for on-site refuse collection;

(b) Where a development has a gross floor area of less than 1,500m², and waste collection will occur not more than twice per week, a WCV parking space provided on site may be considered to satisfy the requirement to provide on-site parking for another service vehicle type that is not larger than the WCV.

Land Use	Car spaces	Service vehicle spaces	Cycle spaces
		>200m ² GFA)	GFA + 1 visitor space / 50m ² GFA
Health care services	1 space / 20m ² GFA	- Where requiring access via a road – SRV (Type A Access) + occasional access for MRV - Where requiring access via a street – SRV (Type B Access) + occasional access for MRV	1 employee space / 100m ² GFA + 1 customer space / 100m ² GFA
Market	1 space / 20m ² total use area	WCV	1 employee space / 100m ² total use area + 1 customer space / 100m ² total use area
Service Station	1 space / 20m ² GFA (when involving sale of goods) + 2 spaces / service bay (min. 4 spaces)	AV	1 employee space / 190m ² GFA + 1 customer space / 475m ² GFA
Shop ³	1 space / 20m ² GFA	- Where ≤ 200m² GFA – SRV - Where 201m² to 600m² GFA – VAN + MRV - Where ≥ 600m² GFA – 1 VAN + 1 SRV + 1 MRV	
Shopping Centre ²	1 space / 20m ² GFA (where ≤ 1,000m ² GFA) + 1 space / 25m ² GFA for component above 1,000m ² GFA)		
Veterinary Hospital	1 space / 20m ² GFA	- Where requiring access via a road – SRV (Type A Access) + occasional access for MRV - Where requiring access via a street – SRV (Type B Access) + occasional access for MRV	
Indoor Sport and Recreation	Sufficient spaces to accommodate the number of vehicles likely to be	Sufficient spaces to accommodate number of vehicles likely to be	Sufficient spaces to accommodate number of vehicles likely to

³ (a) Where gross floor area exceeds 200m², provision is to be made for on-site refuse collection;

(b) Where a development has a gross floor area of less than 1,500m², and waste collection will occur not more than twice per week, a WCV parking space provided on site may be considered to satisfy the requirement to provide on-site parking for another service vehicle type that is not larger than the WCV.

Land Use	Car spaces	Service vehicle spaces	Cycle spaces
	parked at any one time (with min. 1 space / 20m ² GFA in Sub-Precinct 2.8 and min 1 space/15m ² in all other sub-precincts)	parked at any one time (with min. 1 WCV bay)	be parked at any one time
Outdoor Sport and Recreation	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time	- Where requiring access via a road – MRV (Type A Access) + WCV; - Where requiring access via a street – MRV (Type B Access) + WCV	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time
Service Industry	1 space / 50m ² GFA (where ≤500m ² GFA) + 1 space/100m ² GFA (for component >500m ² GFA)	- Where requiring access via a road – AV (Type A Access) - Where requiring access via a street – AV (Type B Access)	1 employee space / 500m ² GFA
Display Unit	1 covered space	Not required	Not required
House			
Display Home			
Multiple Residential (duplex)	1 space / dwelling or unit	Not required	Not required
Multiple Residential (other than duplex)	1 space / dwelling or unit + 1 visitor space / 4 dwellings or units	- Where < 10 dwellings and requiring access via a street – MRV (Type B Access) + VAN - Where > 10 dwellings or requiring access via a road – MRV (Type A Access) + VAN + WCV	1 resident space / dwelling + 1 visitor space / 4 dwellings
Other Residential	1 space / unit (covered) + 1 visitor space / 10 units in Sub-Precinct 2.8 or 1 visitor space / 5 units in all other sub-precincts.	- Where ≤ 20 dwellings and requiring access via a street – MRV (Type B Access) + VAN + ambulance - Where > 20 dwellings or requiring access via a road – MRV (Type A Access) + VAN + WCV + ambulance.	1 resident space / unit + 1 visitor space / 10 units
Short-term accommodation <i>Note - where the short-term</i>	1 space / rooming unit (covered) + 1 visitor space / 10 rooming units	Where ≤ 20 rooming units and requiring access via a street – MRV (Type B Access)	1 resident / employee space / 10 rooming units + 1 visitor space / 20 rooming units

Land Use	Car spaces	Service vehicle spaces	Cycle spaces
<i>accommodation is in the form of a multiple residential (other than a duplex), the parking rates specified for multiple residential (other than a duplex) apply.</i>		+ VAN Where > 20 rooming units or requiring access via a road – MRV (Type A Access) + VAN + WCV;	
Showroom	1 space / 20m ² GFA (where ≤100m ² GFA) + 1 space / 50m ² GFA (for component >100m ² GFA)	- Where ≤ 200m² GFA – SRV - Where 201m² to 600m² GFA – VAN + MRV - Where ≥ 600m² GFA – 1 VAN + 1 SRV + 1 MRV	1 employee space / 100m ² GFA + 1 customer space / 100m ² GFA
Telecommunications Facility	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time (min. 1 space)	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time	Not required
Car Park	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time	Not required	Not required
Integrated Tourist Attraction	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time	Sufficient spaces to accommodate number of vehicles likely to be parked at any one time
Notes (1) Type A Access – where the design vehicle access must:- (i) enable entering and exiting the site in a forward motion; (ii) enable travel through the site on circulation roads / aisles to access service areas, without significant impact on external or internal traffic operations; and (iii) enable on-site manoeuvring to park and load / unload in a designated service area. (2) Type B Access – where the design vehicle access must:- (i) enable standing wholly within the site without occupying any designated queue areas, or blocking access to more than 50% of car parking spaces; and (ii) limit any on-street manoeuvring to reversing on or off the site in one movement only. The swept path of the vehicle may cover the overall width of a two-way undivided driveway. (3) Where a development is for a residential activity or community activity use, and waste collection will occur not more than twice per week, a WCV parking space provided on site may be considered to satisfy the requirement to provide on-site parking for another service vehicle type that is not larger than the WCV. (4) Occasional access (for the maximum size of service vehicle expected less than 20 times per year) is to be provided for vehicles that occasionally service a site as part of its normal operation. Examples of this type of servicing are a furniture removal van at a multiple dwelling or office development and a refuse collection vehicle at a community activity facility. Vehicle access must:- (i) enable standing wholly within the site; (ii) enable reverse manoeuvres limited to one only, either to or from the site; and (iii) enable the swept path of the vehicle to be not greater than the width of the access driveway.			

Appendix I

District Centre Plan of Development Ref I67I00-2I-50X,
Mixed Use Site Plan of Development Ref I67I00-2I-I32P and
Temporary Sales & Display Villages Plan of Development Ref
I67I00-I48H

RPS

Appendix J

School Plans of Development:

State High School Site - Ref I67I00-2I-I06P and

Primary School Site - I67I00-2I-I08V

RPS

Appendix K

Road Hierarchy Ref I67I00-2I-I07_6Z and
Road Sections I67I00-30N Sheets I to 25
RPS

Appendix L

Eco-Centre Precinct Plan of Development Ref I67I00-2I-I33N
RPS