



GROUND WORKS

EXISTING TREE REMOVAL

				Ī		Charles Charles
Photo	Pot Size	Botanical Name	Common Name	Qly	ē	Image
						Plant List
	45Li i re	Elaeocarpus eumundi	Smoothed leaved Quandong	_	ELA EUM	
						Trees
Photo	Pot Size	Botanical Name	Common Name	Qty	Б	Image
						Plant List

0 ALP MUT 49 Dwarf Ginger Alpinia mutic

PHI RCO HRN 27 Hot Rio Nights Rojo Congo Rio Nights Philodendron Rojo Congo

0

RAP EXC PIT WDW PHI XAN 8 14 81 Lady Palm Wheeler's Dwarf Japanese Mock Orange Pittosporum tobira k "Wheeler's Dwarf" Raphis Philodendron Xanadu

Plant List round Image 0 CAS CIT ₽ QTy 4 Common Name Cousin It Botanical Name Casuarina Cousin It Pot Size 140mm hoto

0 0 DIC SFA LOM SWA LIR JRI 3 76 12 Silver Falls Green matrush Just Right Lomandra hystrix Liriope Just Right Dichondra Silver Falls 140mm 140mm 140mm

DEVELOPMENT APPROVAL Approval no: DEV2024/1488 ANS AND DOCUMENTS ferred to in the PDA 30/09/2024

4000

TRA JAS

mum

140mm

Plant Quality
Plants to have
Plants to be fre

olerance: Max 15i

asminoides



Clearing and grubbing
Grubbing: Grub out stumps and roots over 75mm diameter to a minimum have been grown in their final containers in environmental conditions similar cled for where they will be planted, for min 42 days before Site delivery, planted in the sun are to be previously 'sun grown' or 'sun hardened', for min

—2 X HARDWOOD STAKES
1800x50x50mm, AND TIE
IN FIGURE OF 8 PATTERN
USING HESSIAN TIE

MULCH

TOPSOIL

I label each plant by botanical name, commog 20% of the lesser foliage side. aspect of trees in the Nursery to be identified & trees planted with this side facn

e & plant characteristics, on a durable weather-proof tag.

Stock: Not to have co-dominant stems. To have crown foliage symmetry with no

Finished grou

Soil organic matter to be 6-8% by mass. Topsoil particle size criteria are to meet AS 4419. Topdressing materials are to meet AS 4419.

Composts, Soil Conditioners & Mulches;
Test both imported topsoil & potting mixes to AS 1289 (Methods of Testing Soil) & AS 3743. Topsoil to contain organic matter 64% by mass & have sandy loam texture to AS 4419.

nply with AS 4419 'Soils for Landscaping'. Soil conditioner to AS 4454 bil Conditioners & Mulches'.

Below finished surface in unpaved areas: 300 mm.

Backfilling: Fill holes remaining after grubbing with sand material to prevent ponding of water. Compact the material to the relative density of the existing

Below subgrade under buildings, embankments or paving: 500mm.

TOPSOIL

led opasol mix to comply with the following:
Contain organic matter which supports plant life.
Components to be evenly distributed throughout the mix.
Mixes to be mechanically screened prior to despatch using screen size.

-CSmm, this to be moist but still free flowing & of such mosture content that water cannot be squeezed from it by hand.
Material to be void of ingredients which display high shirtkage tendencies.
Reper addict douter (flouding those caused by excessive ammonia or organ acids), chemicals & toxins defininghal to plants & human touch. Free of stones, clay lumps, weeds and weed propagules including Cyperus Rotundus (nul-grass tubers), tree roots, sticks, rubbish, sharp items & other controls of the control of the contr

and the larval stage of insect pests Topsoil Spreading foreign matter.
Free of pests and diseases such as pathogenic organisms e.g. Phytophthora spp

Topsoil to grassed and turfed areas: 100mm (min) thick.
Topsoil to planting areas: 300mm (min) thick (add 75mm to this min thickness for

planting area crown).

Crown topsoil in planting areas.

Lightly consolidate topsoil to a smooth surface, free from lumps of soil and roots, ready for planting.

Progressively layer (max 100mm compacted thickness) & tamp topsoil to prevent voids & subsidence. Prevent excess compaction. topsoil to subsided topsoil (including during the Defects Liability Period) to bring

Cultivate to loosen the existing ground to subsequently receive topsoil. Cultivation depth for subsequent grasses danes: \$50mm deep. Cultivation depth for subsequent plants & planting areas: 300 deep. Break-up cultivated earth so that pieces are less than \$50mm. Remove stones exceeding \$50mm, and any other debelerous nativated from cultivated earth including roots, stocks. CULTIVATION

SYZ RES

ß

Syzygium Resilience

MATERIALS
2.1 MATERIAL COMMON DETAIL
Provide plant life in healthy condition, without scarring or deformations. Establish plant life for optimum growth for the environmental conditions.
Continuously Work is keep plant life fee of disease, and free of plant (weeds) & animal conditions.

On the plant life is a plant life fee of disease, and free of plant (weeds) & animal plant life.

On the plant life is a plant life in the plant life is a plant life in the plant life is a plant life. SOFT LANDSCAPING

deletious and extraneous matter including sof, weeds, sticks, roots, Mulch to be seved to size to prevent accumulation of mulch fines.

Spread mulches eventur in a main about a company and a company prevent accumulation of mulch fines.

evenly to a min depth of 100mm, UDO. Grade the finished surface
lace mulch in contact with stems of plants.

- AGED FOREST MULCH

Type - WINTERGREEN

Turf to be free from weeds & other foreign matters. Turf to be comprised of consistently thick grass & root (fully so led) parts. Grass part to be 20mm thick, root part to be 25mm thick.

Evenly mix fertilizer into the topsoil before placing the turf.

Lay turf within 24 hours of cutting. Prevent turf from drying out between cutting and

Lay furf along land contours with staggered, but joints. Immediately after laying, roll turf with a 90 kg/m roller. Fill joints & depressions with topsoil. On stopes too steep for rolling, evenly tamp the furf. diately after rolling, irrigate with a fine spray so that the soil is moist to a depth of

flush with adjacent surfaces. Grade falls evenly. Turf surface to be smooth &

When it if is established move at Zerom above soil level, remove cutings & top dress reax (form deep with logatilio fill joints and cornect strates unevenness. The contract strategy at minimum of 10 gim2 of sulphate of ammonia fertiliser over the whole of the erea of furfug.

ually extract weeds that emerge in the turfed areas. Where necessary spray with a crive broad leaf weed herbicide. we well-balanced branching foliage typical of their species for the season, if free from pests, diseases, physiological disorder & nutritional deficiency, ially free from evidence of any previous disorder. 15mm under a 3000mm straight edge any direction.

deliver plants in pathogen free, weed free medium. t roots to be undamaged, unrestricted, well-proportioned in relation to the size of thu cycled polypropylene containers or polythene bags silows, UDO:

eath & around the plant root: system, UDO:

Plant Height at time of planting (excluding the root ball - mm) Thickness/depth of topsoil around the root ball 100

EXCAVATE PLANT HOLE 2 X DIAMETER OF ROOT

CULTIVATE SUB-GRADE SLOW RELEASE FERTILISER OR PELLETS

THAN DEPTH OF POT BALL AND GREATER

SETTLEMENT
-WATER PLANT HOLE THOROUGHLY BEFORE AND AFTER PLANTING

water the planting hol

Sht-3

Scale: 1:40

TREE PLANTING DETAIL

Form watering – basin by mounding soil around edge

Finished ground level

and allow water to drain away prior to installing plant. Water plant and plant hole after planting. Fill excavated plant hole with water

ball, and greater than soil depth of pot Excavate plant hole 2 x diameter of roo Place slow release prolonged release type fertilizer around plants at the time of planting. Backfill with topsoil to be firm around the plant without air pockets. Dish the soil around tion plants in the centre of planting holes. Set plants plumb & at a level for natural ionship of the plant with the ground surface.

blanks for water capture (dist damater to match port diamater or noot ball).

For plants to be one 2000mm tall at matchity, vertically permoted in the backfill, a 75mm (dis. 300mm length of black colour, shotled agricultural drain pipe behind the plant (portuding above the much 20mm) as a deep watering mechanism. Place much to 50mm deep in the base of the pipe.

Commence planting immediately after Ste delivery.

If unforessen planting immediately after Ste delivery.

If unforessen planting objects occurs transletin plants into larger pots, and a more plant plant and a more plant p

Install slow release fertiliser pellets
into plant hole
at time of planting

Plants with stems or trunks to be staked to give plant support. Stakes to be straight, undamaged, have flat top ennts & pointed driving ends. Stakes & components (lies, care) to be of a neutral & natural colour (le grey, black, brown) which can be achieved by painting. Cap all stakes after their placement, with a neutral & natural coloured wired-on plastic

Single sakes to positioned behind the plant (le opposite the likely pedestrain traffic side), double stakes to be positioned evently apart & parallel to the likely pedestrain traffic side, triple stakes to be positioned evenly apart with 2 takes positioned behind the plant (le opposite the likely pedestrain traffic side).

The plant to each stake at the top 10% of the exposed to view stake. The also as required

es & ties no longer required to support the plant, at the end of the Defects

			Plastic ties: Proprietary ties.	Plastic ties: P
Hessian	600/1800	50x50 HWD	ω	1800-2400
Hessian	400/1200	50x50 HWD	ω	1500-1800
	Exposed Height			planting-mm)
& Type	ground Depth/		Number	(at time of
Ties	Stake In-	Stake Size(mm)	Stake	Plant Height

Steel rope ites: 3mm dia galv steel wire rope, cut ends steel clamped, turnbuckle tension adjustment, plastic guards against frunk, the loop dia around frunk to be 3 limes fhe dia of the trunk at that be point.

2.6 MAINTENANCE

Mainfain construction Work. After Practical Completion, mainfain the Work for 12

WEEKS to the doc standard. Maintenance induses:

Watering facilitying pest & disease control.

Mawing wearing seraind, removal of cultings

Pruning (to As 473) the intention of pruning being to maintain healthy foliage or remove damaged growth.

Replacing damaged of falled planting.

Replacing hubb maintenance
Staff replacement freetpring much maintenance
Mantenance and establishment plan
The landscape confracting its outbring to proposed maintenance and establishment plan
The landscape confracting its outbring to proposed maintenance and establishment plan
plan prior to the staff of the establishment period. The landscape confractor is on maintain a
log book of activities underticated on site during the planting and establishment for
presentation to the superintendant.

M: 0407 114 605 (B.App.Sc.Blt.Env, Grad.Dip.Lands.Arch.) Registered Landscape Architect AlLA no.1132 ABN: 41 134 988 971 PO BOX 373, ANNERLEY QLD 4103

> Drain planter to outlet. Install protection board/sheeting over walls to planter box. under tree root ball Tanked and sealed falls to drainage outlets Sht-3 Base of planter Reduce bedding sand layer depth Medium bedding to 50mm depth 10 PLANTER BOX Sht-3 Scale: 1:25 sand layer SHRUB, GROUNDCOVER PLANTING DETAIL
> Scale: 1:20 tanking 75 100 VARIES(REFER ARCHITECT DWG) riser pipe with grated cap by landscape growing media (Note: tree root ball not Drainage cell with shown). Container Mix Install Podium contractor. Connect to stormwater outlet geofabric over base of overflow drainage Cast-in drain by others (Refer planter PVC perforated hydraulic drawings) 75mm depth mulch

REVISION

PROVINCIAL

E: baldock@bigpond.net.au

IŠSUE ĎĂŤĚ REVISION
PROJECT:
67 SHORE ST, CLEVELAND QLD

SPECIFICATION CONCEPT PLANT LIST, SCALE: AS SHOWN SHEET SIZE: AS PROJECT NO: **2402** REVISION: C DWN Design Certified by: MBaldock Sht-3