

Portside Site, Hamilton - Recorded Short-Term Statistical Noise Levels


P&O Noise Levels

Noise Source	Locn	Level	Notes
Loading Bang		65.3 dB(A)	at 300m
Loading Bang		68.2 dB(A)	
Loading Bang		63.4 dB(A)	at 250m
Forklift		63.0 dB(A)	at 250m
'Alblasgracht' at Hamilton 1 Leaving Port	1	73.0 dB(A)	at 75m for 6 minutes
Alarm		61.1 dB(A)	at 250m
Cranes		62.0 dB(A)	at 225m
Reversing Beeper		63.0 dB(A)	at 200m
Horn		61.7 dB(A)	at 200m
Loading Bang		58.4 dB(A)	at 250m
Loading Bang		58.3 dB(A)	at 250m
Loading Bang		58.2 dB(A)	at 250m
Cranes		60.0 dB(A)	at 200m
P&O Trucks		60.0 dB(A)	at 200m
Reversing Beeper		60.0 dB(A)	at 200m
Loading Bang		57.6 dB(A)	at 250m
Loading Bang		57.2 dB(A)	at 250m
Loading Bang		55.8 dB(A)	at 250m
Loading Bang		55.5 dB(A)	at 250m
Chain Rattle		60.0 dB(A)	at 130m
Loading Bang		54.2 dB(A)	at 250m
Forklift	8	59.5 dB(A)	at 130m
Reversing Beeper		54.5 dB(A)	at 200m
'Alblasgracht' Generator		60.0 dB(A)	at 85m
'Alblasgracht' Generator		61.0 dB(A)	at 75m
Reversing Beeper		54.6 dB(A)	at 150m
'Parkgracht' at Hamilton 1 Berthing under tug power	2	61.0 dB(A)	at 70m for 5 minutes
Container Forklift		52.5 dB(A)	at 150m
Forklift		63.6 dB(A)	at 30m
Forklift		52.5 dB(A)	at 100m
'Parkgracht' Generator		54.5 dB(A)	at 75m
Forklift		52.5 dB(A)	at 50m
Scrap Metal Loading		63.0 dB(A)	at 50m


ATTACHMENT 3

Datalogger Noise Traces


Recorded Statistical Noise Levels - Centre of Portside Wharf Site - 7 April, 2003




Recorded Statistical Noise Levels - Centre of Portside Wharf Site - 8 April, 2003




Recorded Statistical Noise Levels - Centre of Portside Wharf Site - 9 April, 2003




Recorded Statistical Noise Levels - Centre of Portside Wharf Site - 10 April, 2003




Recorded Statistical Noise Levels - Centre of Portside Wharf Site - 11 April, 2003




Recorded Statistical Noise Levels - Centre of Portside Wharf Site - 12 April, 2003




Recorded Statistical Noise Levels - Centre of Portside Wharf Site - 13 April, 2003




Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 7 April, 2003




Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 8 April, 2003




Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 9 April, 2003




Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 10 April, 2003




Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 11 April, 2003




Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 12 April, 2003



Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 13 April, 2003



Recorded Statistical Noise Levels - Hercules St Frontage of Portside Wharf Site - 14 April, 2003



ATTACHMENT 4

SoundPLAN Validation Model

Signs and symbols

- Road axis
- Emission line
- Surface
- Bridge
- Wall
- Point receiver

Hamilton 06-128
Portside Wharf

Year 2003 Model Layout

Validation Point Location
Ground Level



© 2006 Europa Technologies
Image © 2006 DigitalGlobe

Hamilton Portside Wharf Validation Model

Project description

Project title: Portside Wharf Development - Hamilton
Engineer: Travis Carberry
Customer:

Description:

Run description

Calculation: Single Point Sound
Title: 2003 Validation
Run file: Portside.runx
Result number: 10
Calculation start: 1/05/2008 9:18:59 AM
Calculation end: 1/05/2008 9:19:00 AM
Calculation time: 00:00:094 [m:s:ms]
No. of points: 1
No. of calculated points: 1
Kernel version: 18/03/2008 (RKernel7.dll)

Run parameters

Reflection order: 3
Maximal reflection distance to receiver: 200 m
Maximal reflection distance to source: 50 m
Search radius: 5000 m
Weighting: dB(A)
Tolerance: 0.001 dB

Standards:

Roads: Calculation of Road Traffic Noise (UK)
Emission according to: CRTN

Assessment: CRTN L10

Reflection of "own" facade is suppressed

Geometry data

RDGM0001.dgm 8/2/2006 9:29:32 AM
Validation.sit 8/2/2006 4:08:42 PM
- contains:
Contours.geo 6/26/2007 9:40:44 AM
Datalogger.geo 8/2/2006 4:08:42 PM
Hercules St 2003.geo 8/2/2006 4:03:28 PM
Kingsford Smith Drv 2003.geo 8/2/2006 3:15:38 PM
Remora Rd 2003.geo 8/2/2006 4:03:28 PM

Hamilton Portside Wharf Validation Model

Receiver	Usage	Floor	Dir	L10(18h) dB(A)	
Datalogger	WA	EG		61.1	

ATTACHMENT 5

Year 2020 SoundPLAN Modelling

Signs and symbols

Road axis

Emission line

Surface

Bridge

Wall

Main building

Point receiver

Geometry bitmap

Hamilton 10-088
Portside Wharf
Building 6 DA

Year 2020 Model Layout

Building Receiver Locations
Levels 1-14



Portside Wharf Development - Hamilton - Year 2020 Predictions - Building 6 DA

Project description

Project title: Portside Wharf Development - Hamilton
Engineer: Travis Carberry
Customer:

Description:

Run description

Calculation: Single Point Sound
Title: Year 2020 Predictions - Building 6 DA
Run file: Portside.runx
Result number: 400
Calculation start: 8/5/2010 1:50:19 PM
Calculation end: 8/5/2010 1:50:20 PM
Calculation time: 00:00:858 [m:s:ms]
No. of points: 5
No. of calculated points: 5
Kernel version: 7/23/2010 (RKernel7.dll)

Run parameters

Reflection order: 1
Maximal reflection distance to receiver: 200 m
Maximal reflection distance to source: 50 m
Search radius: 5000 m
Weighting: dB(A)
Tolerance: 0.001 dB

Standards:
Roads: Calculation of Road Traffic Noise (UK)
Emission according to: CRTN

Assessment: CRTN L10

Reflection of "own" facade is suppressed

Geometry data

B6 DA - Aug 10.sit 8/5/2010 1:49:18 PM
- contains:
Building 4.geo 6/26/2007 9:40:44 AM
Building 6.geo 8/5/2010 1:49:18 PM
Contours.geo 6/26/2007 9:40:44 AM
Hercules St 2020.geo 7/23/2010 3:49:00 PM
Kingsford Smith Drv 2020(1).geo 7/23/2010 3:49:00 PM
Remora Rd 2020.geo 7/23/2010 3:49:00 PM
Site Buildings July 10.geo 7/23/2010 4:07:10 PM
RDGM0001.dgm 8/2/2006 9:29:32 AM

Portside Wharf Development - Hamilton
Assessed receiver levels - Year 2020 Predictions - Building
6 DA

21

Name	Usage	Floor	Dir	L10(18h) dB(A)	
Building 6 East	WA	1. Floor	E	60.4	
		2. Floor		61.6	
		3. Floor		61.8	
		4. Floor		61.8	
		5. Floor		61.7	
		6. Floor		61.7	
		7. Floor		61.5	
		8. Floor		61.4	
		9. Floor		61.3	
		10. Floor		61.2	
		11. Floor		61.2	
		12. Floor		61.8	
Building 6 North	WA	1. Floor	N	69.5	
		2. Floor		69.4	
		3. Floor		69.3	
		4. Floor		69.2	
		5. Floor		69.2	
		6. Floor		69.1	
		7. Floor		69.1	
		8. Floor		69.1	
		9. Floor		69.1	
		10. Floor		69.1	
		11. Floor		69.1	
		12. Floor		69.2	
Building 6 Podium Units	WA	1. Floor	N	69.8	
		2. Floor		69.8	
Building 6 South	WA	1. Floor	S	39.8	
		2. Floor		39.9	
		3. Floor		40.3	
		4. Floor		41.3	
		5. Floor		43.9	
		6. Floor		47.2	
		7. Floor		49.0	
		8. Floor		50.2	
		9. Floor		51.2	
		10. Floor		52.1	
		11. Floor		53.3	
		12. Floor		56.4	
Building 6 West	WA	1. Floor	W	63.5	
		2. Floor		64.1	
		3. Floor		64.4	

21

1. The first part of the document discusses the importance of maintaining accurate records of all transactions, including sales, purchases, and expenses. It emphasizes the need for a systematic approach to record-keeping, such as using a ledger or accounting software, to ensure that all financial data is properly documented and organized.

2. The second part of the document focuses on the process of reconciling bank statements with the company's internal records. It outlines the steps involved in comparing the bank's records with the company's books, identifying any discrepancies, and investigating the causes of these differences. This process is crucial for ensuring the accuracy of the company's financial statements and detecting any potential errors or fraud.

3. The third part of the document addresses the issue of budgeting and financial planning. It discusses the importance of setting a realistic budget for the company's operations and how this budget can be used to monitor and control expenses. It also touches on the role of financial planning in making informed decisions about the company's future growth and investment opportunities.

4. The fourth part of the document covers the topic of tax compliance. It explains the various tax obligations that a company may have, such as income tax, sales tax, and payroll taxes, and provides guidance on how to ensure that these obligations are met accurately and on time. It also discusses the importance of keeping up-to-date with changes in tax laws and regulations.

5. The fifth and final part of the document discusses the importance of regular financial reviews and reporting. It emphasizes the need for management to regularly review the company's financial performance, analyze trends, and make adjustments as needed. It also discusses the role of financial reporting in providing transparency to stakeholders and facilitating informed decision-making.

PLANS AND DOCUMENTS
referred to in the ULDA
APPROVAL dated 12/10/10

ENGINEERING REPORT

FOR THE PROPOSED
PORTSIDE WHARF – BUILDING 6

LOCATED AT
36 HERCULES STREET
HAMILTON

PREPARED FOR
CITIMARK PROPERTIES PTY LTD
BY BORNHORST & WARD PTY LTD

AUGUST 2010

Bornhorst & Ward Project No. **10211**

If you have any queries regarding this report please contact Kris Rensch.

Revision	Date	Description	Author	Rev.	App.
C	Aug 2010	Issue to ULDA – Architectural Amended	KR	NR	NR
B	Aug 2010	Issue to ULDA – Architectural Amended	KR	NR	NR
A	Aug 2010	Issue to ULDA	KR	NR	NR
Draft	July 2010	Draft Issue	KR	NR	NR

COPYRIGHT: This document is and shall remain the property of Bornhorst & Ward Pty Ltd and shall not be copied in whole or part. Unauthorised use of this document in any form is prohibited.

File Name: J:\2010\10211\docs\r100705kr - Engineering Report (A).doc

CONTENTS

1.	INTRODUCTION	1
2.	SITE CHARACTERISTICS	1
2.1	LOCATION	1
2.2	LANDUSE	2
2.2.1	EXISTING	2
2.2.2	PROPOSED	2
2.3	TOPOGRAPHY & SITE DRAINAGE	2
3.	SITE DATA	2
3.1	SOURCES OF INFORMATION	2
4.	EXISTING AND PROPOSED CIVIL WORKS AND INFRASTRUCTURE	2
4.1	STORMWATER	2
4.2	EXTERNAL SEWER	3
4.2.1	EXISTING INFRASTRUCTURE	3
4.2.2	SEWER LOADING	4
4.2.3	SEWER CONNECTION OPTIONS	5
4.3	INTERNAL SEWER	5
4.4	WATER	5
4.5	NON CIVIL SERVICES	6
4.6	EARTHWORKS	6
4.7	SITE FLOODING & OVERLAND FLOW	6
4.8	EROSION AND SEDIMENT CONTROL PLAN (ESCP)	7
4.9	ASSET HANDOVER	7
5.	STORMWATER MANAGEMENT PLAN	7
5.1	STORMWATER OBJECTIVES	7
5.2	CATCHMENT DESCRIPTION	7
5.2.1	EXISTING AND PROPOSED	7

5.3	LEGAL POINT OF DISCHARGE	7
5.4	OPPORTUNITIES AND CONSTRAINTS	8
5.4.1	SITE OPPORTUNITIES	8
5.4.2	SITE CONSTRAINTS.....	8
6.	STORMWATER QUANTITY	8
6.1	STORMWATER DRAINAGE METHODOLOGY	8
6.2	PEAK FLOW CALCULATIONS.....	8
7.	STORMWATER QUALITY	9
7.1	WATER QUALITY	9
7.2	SITE CHARACTERISTICS AND IMPACTS.....	10
7.3	PROPOSED TREATMENT TRAIN.....	10
7.4	WATER QUALITY MONITORING PROGRAM	10
8.	SUMMARY.....	10
9.	REFERENCES.....	11

APPENDICES

- Appendix A Figures and Drawings
Appendix B Hydraulic Calculations

LIST OF FIGURES

Figure 1: Orientation Plan (www.nearmap.com)	1
Figure 2: BCC Bimap Stormwater Records.....	3
Figure 3: BCC Bimap Sewer Records.....	4
Figure 4: BCC Bimap Water Records.....	6
Figure 5: Locality Map	2

LIST OF TABLES

Table 1: Sewer Flow Calculations	4
Table 2: Pre & Post Development Peak Flow Calculations	9

1. INTRODUCTION

Bornhorst and Ward has been commissioned to investigate and report on the Civil Engineering and Servicing requirements pertaining to the proposed Portside Wharf – Building 6, located at 36 Harbour Road, Hamilton. The location of the proposed site is indicated in Figure 5, Appendix A.

The Engineering requirements for this proposal shall be in accordance with Brisbane City Council Subdivision and Development Guidelines and the Brisbane City Council City Plan. This report outlines the preliminary design methodology and calculations in support of a Development Application and should be read in conjunction with other documents issued by the consultant team.

2. SITE CHARACTERISTICS

2.1 LOCATION

The proposed site is located on the northern side of the Portside Wharf Cruise Port Terminal development, adjacent to Hercules Street. The site is bound by the existing Portside development on the eastern and southern boundaries, the existing DPI property on the western boundary and Hercules Street on the northern boundary. This is indicated in the figure below.

Street Address: 36 Hercules Street, Hamilton
RP Description: Lot 907 SP 169072



Figure 1: Orientation Plan (www.nearmap.com)

2.2 LANDUSE

2.2.1 EXISTING

The site is currently vacant, and has been excavated to form a temporary carpark adjoining the existing Portside development. Access to the site is via a ramp grading down from Hercules Street. The majority of the site is covered with impervious areas, however there is a mulched earthworks batter transitioning from the Hercules Street level of approximately RL 3.0m to the carpark level of RL 1.0m.

2.2.2 PROPOSED

The proposal detailed in this report is for the construction of Building 6, a 15 level residential building consisting of 208 units, surrounding podium area, single basement level and retail / commercial uses on the ground floor. The site area is approximately 0.267Ha. The proposed site layout is shown on the Cottee Parker architectural drawings, attached in Appendix A.

2.3 TOPOGRAPHY & SITE DRAINAGE

In existing conditions prior to surrounding development works, the site was relatively flat with levels around RL 3.0m. As a result of the previous development, excavation has occurred to form a low set temporary carparking area adjoining the existing Portside carparks, at approximately RL1.0. Surface water is currently collected by two field inlets within the site and directed through the existing Portside drainage system, where it is then discharged to the Brisbane River.

3. SITE DATA

3.1 SOURCES OF INFORMATION

In order to collate existing information for the site and immediate environment, the relevant Council and governing authorities were contacted to determine whether any of the following documents, relevant to the area immediately adjacent to the development, exist:

Waterway Management Plans	- NIL
Catchment Management Plans	- NIL
Stormwater Management Plans	- SKM Site Based Stormwater Management Plan (August 2003)
	- Bornhorst and Ward Master Plan 2 (December 2006)
Flood Studies	- NIL
Infrastructure Charges Plans	- NIL

4. EXISTING AND PROPOSED CIVIL WORKS AND INFRASTRUCTURE

4.1 STORMWATER

There is existing stormwater infrastructure within the road reserves fronting the development site, and within the site itself. These are summarised as follows, and illustrated in the figure below:

- There are a number of gully pits and 600mm diameter stormwater lines within Hercules Street, close to the development site. This infrastructure then discharges to a twin 1200mm diameter stormwater

line within Hercules Street and Remora Road. Stormwater is then discharged to the Brisbane River via a 2100 x 2700mm box culvert.

- There are a number of field inlets and 150mm diameter stormwater lines within the existing carpark on the site. These drain into pipework within the existing Portside development, where stormwater is then pumped through to the outlet into the Brisbane River.




Figure 2: BCC Bimap Stormwater Records.

It is proposed that a stormwater connection is made to the existing gully pit within Hercules Street fronting the development site (Refer drawing SKC010 attached in Appendix A). As the development proposal will not increase the rate in runoff from the site, it is anticipated that this existing infrastructure has sufficient capacity. All hydraulic drainage from podium areas and basement can be directed to this location. This will form the legal point of discharge for the site.

Another option has been considered for connection into the existing stormwater drainage within the carpark area. This would not be desirable, as it will require permission from the adjoining property owner.

Refer to Section 5.0, "Stormwater Management Plan" for further details.

4.2 EXTERNAL SEWER

The existing sewer infrastructure and options for sewer connection are discussed in the following sections.

4.2.1 EXISTING INFRASTRUCTURE

From previous discussions with Queensland Urban Utilities (formerly Brisbane Water), it is understood that the existing sewer infrastructure in the area is nearing capacity. Directly fronting the site, there is an existing 225mm diameter sewer in Hercules Street. This line follows Hercules Street and connects into the existing 300mm diameter sewer in Remora Road. This is indicated in the figure below:




Figure 3: BCC Bimap Sewer Records

There is also a 400mm diameter PE sewer in Macarthur Avenue, recently constructed as part of the Northshore Hamilton Stage 1 works. This follows Macarthur Avenue, and discharges into the existing pump station at the end of Barcham Street. The sewer has been designed to cater an external catchment, consisting of the Hamilton Harbour and Portside Developments.

The Hamilton Harbour development will discharge directly to the S1 sewer in Kingsford Smith Drive, hence leaving additional spare capacity in the Northshore Sewer. This line is however limited by the capacity of the exiting pump station near Barcham Street. Queensland Urban Utilities has advised that there is spare capacity of approximately 1000 EP within the pump station. Preliminary designs have been completed for construction of a trunk sewer from the Macarthur Avenue line, connecting directly to the Violet Street Sewer Pump Station, however the construction timing of this is currently unknown.

4.2.2 SEWER LOADING

A preliminary calculation of sewer loading for the development has been calculated at 7.3L/s (under Peak Wet Weather Flow) in Table 1 below. Calculations have been based on the Brisbane City Council Sewerage Standards and the Water Services Australia Sewerage Code.

Table 1: Sewer Flow Calculations

Area Classification	Units	EP Loading / unit	Total EP
Residential	208 units	2.5 EP / unit	520.0
Retail / Commercial	440m ² NLA	152 EP/Ha	6.7
PWWF (1200L/EP/day)			7.3 L/s

4.2.3 SEWER CONNECTION OPTIONS

Options for the development's sewer connection have been identified as follows. The preliminary location of sewer options is shown on the Services Plan SKC010 attached in Appendix A.

- Option 1
The preferred option is for connection into the existing 225mm diameter sewer directly fronting the site. This is dependant on a capacity assessment and permission from Queensland Urban Utilities. This option has been discussed with Queensland Urban Utilities and is currently under review.
- Option 2
The second option is to connect to the existing Macarthur Avenue sewer by extending a new 150mm diameter sewer along Hercules Street and Remora Road. The total length of new sewer is approximately 200m. Cost sharing of this option between surrounding developers is also a possibility.

As discussed in previous sections this existing Northshore line has been designed with sufficient capacity for this catchment, but is however limited by the capacity of the existing downstream pump station, until such time that the trunk infrastructure connecting sewer to the Violet Street Pump Station is constructed.

- Option 3
The third option is for extension of a new 150mm diameter sewer line within Hercules Street and Remora Road which connects into the S1 sewer in Kingsford Smith Drive. This would involve construction of approximately 150m of sewer. Construction difficulties in terms of traffic management within Kingsford Smith Drive may arise.

Discussions with Queensland Urban Utilities regarding these options have commenced. Preliminary advice has also been received from QUU, indicating that based on their assessment the sewer connection to the existing Hercules Street sewer is allowable (Option 1). This is currently being reviewed by QUU, who have advised that a formal letter will be issued shortly. Once received, this will be forwarded to the ULDA for information.

4.3 INTERNAL SEWER

Design of the sewer internal to the site will be completed by the Hydraulic Engineer. Any internal pumps required to service basement areas will remain the property of the development and not be handed over to council.

4.4 WATER

There is an existing 150mm diameter potable water main within Hercules Street, along the full frontage of the site. There are also two existing 100mm diameter water connections to the site from the existing water main. It is the developer's intention to utilise these water connections as required (Refer drawing SKC010 attached in Appendix A). Flow and pressure tests will be required to determine suitability of this existing connections and main.



Figure 4: BCC Bimap Water Records

Permission is being sought from Queensland Urban Utilities for the water connection. Preliminary advice has been received, indicating that based on their assessment, water connection to the existing 150mm diameter water main in Hercules Street will be allowable. This is currently being reviewed by QUU with a formal letter being issued shortly. Once received, this will be forwarded to the ULDA for information.

4.5 NON CIVIL SERVICES

Non civil services including telecommunications and electricity will be required for the development. There are existing telecommunications services along the Hercules Street site frontage. Overhead power is also present within Hercules Street. The capacity of the existing services on Hercules Street will require assessment by associated consultants.

4.6 EARTHWORKS

Minor earthworks will be required for excavation of the basement level. The majority of the site has been lowered to the existing Portside basement level, hence minor regrading of this area will be required to remove existing batters and ramps. All earthworks will be undertaken in accordance with Brisbane City Council Subdivision and Development Guidelines.

4.7 SITE FLOODING & OVERLAND FLOW

A BCC Floodwise Report has been obtained for the site. The highest defined flood level is RL2.5m AHD as a result of a Storm Tide. Prior to earthworks, the site was approximately RL3.0m. As the Ground Level for the development will be constructed at RL4.7m AHD, with residential areas being above this, the development will not be affected by flooding, and have freeboard, to the highest defined flood level, exceeding 2.2m. Existing levels within Hercules Street, surrounding the site access are in excess of RL3.0m, therefore sufficient freeboard is provided to the basement access.

4.8 EROSION AND SEDIMENT CONTROL PLAN (ESCP)

A comprehensive Erosion and Sediment Control Plan including a construction process will be prepared for this development during the detailed design phase. The ESCP designs will be in accordance with the Institution of Engineers reference material and Brisbane City Council's Guidelines.

4.9 ASSET HANDOVER

It is the intention of the applicant that the stormwater quantity and quality controls detailed in this document, will not be handed over to Council as part of the development's stormwater infrastructure.

5. STORMWATER MANAGEMENT PLAN

5.1 STORMWATER OBJECTIVES

Under the Brisbane City Council Land Use Development Guidelines, several design elements were identified in relation to stormwater management issues. Brisbane City Council must be satisfied that:

- The proposed development can be drained;
- The stormwater management system can follow the features and functions of the natural drainage system;
- The volume, timing velocity and pollutant load of stormwater has no adverse effect on any surrounding properties or receiving waters; and
- Suitable provision is made in the design layout to accommodate for major drainage.

5.2 CATCHMENT DESCRIPTION

5.2.1 EXISTING AND PROPOSED

Prior to excavation, the site was relatively flat with levels around RL3.0m. Surface water discharged to Hercules Street. Since the construction of the existing Portside Wharf development, stormwater is discharged into stormwater drains provided as part of the previous stages, and connects through the existing basement levels. The site in its current state and prior to surrounding development has and had significant amounts of impervious area.

Under development conditions, all stormwater drainage within the site will consist of hydraulics drainage. As site discharges are relatively low it is expected that all flows are collected by the hydraulics system, with little or no overland flow during major storm events.

5.3 LEGAL POINT OF DISCHARGE

The existing point of discharge from the site is the Brisbane River, located towards the south of the development. The legal point of discharge for the development is the existing pipework within Hercules Street. This is discussed further in Section 4.1 above.

5.4 OPPORTUNITIES AND CONSTRAINTS

5.4.1 SITE OPPORTUNITIES

The major opportunities identified for the site with respect to the application of stormwater quality and quantity controls are:

- The use of rainwater tanks to capture roofwater runoff for re-use within the internal plumbing of the buildings.

5.4.2 SITE CONSTRAINTS

The major constraints identified for the site with respect to the application of stormwater quality and quantity controls are:

- High density developments change the runoff characteristics of the development. An increase in impervious area can result in an increased amount of runoff.
- The size of the development site restricts the space available for use in stormwater management.

6. STORMWATER QUANTITY

6.1 STORMWATER DRAINAGE METHODOLOGY

Modelling of stormwater runoff quantity has been considered for the existing case and operational phase of the development. In order to assess the existing and predicted future (operational phase) discharge rates from the development site, calculations have been conducted based on the Rational Method, according to the methods specified in the Queensland Urban Drainage Manual and Brisbane City Council's Subdivision and Development Guidelines.

Calculations have been undertaken to determine the undeveloped and developed peak run-off rates with the Best Management Practices (BMPs) incorporated into the site layout for stormwater quantity control.

6.2 PEAK FLOW CALCULATIONS

The Rational Method as outlined in the Queensland Urban Drainage Manual was used to determine the peak flow rate corresponding to the minor and major storm events for this development. The fraction impervious for the existing and developed conditions have been estimated based on a review of aerial photography and the proposed development layout. The lower fraction impervious in the developed conditions can be attributed to the landscaping area on the Podium level.

Brisbane City Council Subdivision and Development Guidelines, Table B2.1, "Design Standards for Major/Minor Drainage Systems" was used to identify the design storm events for this development as:

Minor -	1 in 10 year ARI
Major -	1 in 50 year ARI
Major (overland flow) -	1 in 100 year ARI

Flow rates were calculated at the point of discharge from the site for the existing and developed phases of the development. Detailed calculations can be reviewed in Appendix B.

Table 2: Pre & Post Development Peak Flow Calculations

	Parameter	Existing	Proposed
Catchment Details	Area (Ha)	0.267	0.267
	Fraction Impervious	90%	80%
	Coefficient of Runoff (C10)	0.88	0.86
	Time of Concentration (min)	5.0	5.0
	10 year Rainfall Intensity (mm/hr)	215	215
	50 year Rainfall Intensity (mm/hr)	292	292
	100 year Rainfall Intensity (mm/hr)	327	327
Discharge	1 in 10 year ARI (m ³ /s)	0.140	0.137
	1 in 50 year ARI (m ³ /s)	0.217	0.214
	1 in 100 year ARI (m ³ /s)	0.242	0.242

As indicated within the table above, the discharge rates from the proposed development are similar to the existing conditions. As landscaping is incorporated in the development plan, the runoff rates for the Q10 and Q50 storm events is slightly lower, hence no stormwater quantity controls are proposed. Due to the close proximity of the site to the Brisbane River, stormwater will be discharged as quickly as possible. The development will however incorporate an 80kL rainwater tank. This has been assumed full for the above calculations.

7. STORMWATER QUALITY

7.1 WATER QUALITY

All references to water quality objectives and design requirements within this report have been based on Brisbane City Council Standards and in particular Brisbane City Council Subdivision and Development Guidelines Part C – Water Quality Management Guidelines.

The Brisbane City Council Subdivision and Development Guidelines, Part C – Water Quality Management Guidelines, specifies that the level of stormwater treatment is determined by the development falling into either the 'high' or 'low' risk categories. For a development to be classified as 'high risk' it must fall within one of the following categories as specified in Section 3.1.1 of the above guidelines:

- Development located in a waterway corridor, Brisbane River corridor, or wetland area;
- Multi-unit dwellings or commercial uses with an impermeable surface area (not including roof area) in excess of 2500m²;
- Subdivision where greater than 6 lots are involved
- Industrial activities that are not impact assessable (under Council's City Plan) and have at least 1000m² in uncovered storage / working space;
- Industrial activities that are impact assessable (under Council's City Plan);
- Uncovered car parks with at least 100 spaces;
- Developments which discharge stormwater or wastewater to an area deemed by Council to have significant environmental value.

From a review of these categories, we believe that the development can be classified as 'low risk' for Water Quality as the site is not located in a waterway corridor, Brisbane River corridor or wetland area. Also, the majority of the site consists of roof areas, hence the uncovered impervious areas within the site will be less than the 2500m² trigger for 'high risk' developments. As the development has been classified as 'low risk' Best Management Practices will be applied.

7.2 SITE CHARACTERISTICS AND IMPACTS

The proposed development is such that the majority of the site is covered with roof area. It is hence expected that the generation of pollutants would be low. Best management practices will be applied to mitigate the pollutant discharge from the site.

7.3 PROPOSED TREATMENT TRAIN

It is proposed to install a GPT in the basement area for treatment of stormwater prior to discharge. We expect that this would be of the Ecosol RSF4000 range which allows trapping of oils and grease. The location of this is to be determined by the Hydraulic Engineer during the detailed design phase.

The development proposal also includes an 80kL rainwater tank, to be located within the basement area. This will provide storage for rainwater to be reused within the site.

7.4 WATER QUALITY MONITORING PROGRAM

As this development discharges stormwater into the existing drainage system using stormwater quality Best Management Practices, no proposal for water quality monitoring has been made. The measures proposed for water quality and water quantity treatment are reasonably well understood and demonstrated in Brisbane. It is hence anticipated that they are acceptable here.

8. SUMMARY

From the investigations conducted, it has been shown that the proposed development located within the Portside Wharf Precinct can be constructed and serviced in accordance with Brisbane City Council requirements, the Queensland Urban Drainage Manual and widely accepted engineering principals.

The Stormwater Management Plan has demonstrated that adequate treatment of stormwater quantity and quality is possible under the proposed plan. Sufficient consideration of stormwater controls has been made to demonstrate the viability of the proposed development.

9. REFERENCES

- 1) Draft Australian Runoff Quality (IEAust 2003).
- 2) Brisbane City Council (1999) – Draft Design Guidelines for Stormwater Quality Improvement Devices.
- 3) Brisbane City Council (2000) Brisbane City Council's Water Quality Management Guidelines.
- 4) Brisbane City Council (2000) Guidelines on Identifying and Applying Water Quality Objectives in Brisbane City.
- 5) Brisbane City Council (2000) – Guidelines for Sediment Basin design, Construction and Maintenance
- 6) Brisbane City Council - Draft WSRD Guidelines (2003)
- 7) Brisbane City Council - Draft Design Guidelines for Stormwater Quality Improvement Devices (1999)
- 8) Brisbane City Council (October 2003) Guidelines for Pollutant Export Modelling in Brisbane – Version 7.
- 9) Water Quality management Guidelines, Part C of Brisbane City Council (2000) Subdivision and Development Guidelines
- 10) Queensland Urban Drainage Manual.
- 11) Model for Urban Stormwater Improvement Conceptualisation User Manual Version 1.00. (CRC-CH 2002).
- 12) A Bibliography of Urban Stormwater Quality (Duncan 1995)
- 13) Soil Erosion and Sediment Control Guidelines for Queensland Construction Sites (1996). The Queensland Division of the Institution of Engineers, Australia.

APPENDIX A

FIGURES AND DRAWINGS






Figure 5: Locality Map

UBD Map: Brisbane UBD, Map 240 - C1



PROJECT PORTSIDE WHARF LAKES DISTRICT SCALE 1:200 DATE 13/06/2008 DRAWN BY AVL CHECKED BY AVL PROJECT NO. 6121-142		CLIENT CITIMARK PROPERTIES BASEMENT LEVEL PROPOSED BUILDING 6 CONTOUR & DETAIL SURVEY JOB NO. 6121-142 BRISBANE CITY COUNCIL 04/08/06	
--	--	---	--

SYMBOLS		LINDWORK	
1. 100m 2. 50m 3. 20m 4. 10m 5. 5m 6. 2m 7. 1m 8. 0.5m 9. 0.2m 10. 0.1m 11. 0.05m 12. 0.02m 13. 0.01m 14. 0.005m 15. 0.002m 16. 0.001m 17. 0.0005m 18. 0.0002m 19. 0.0001m 20. 0.00005m 21. 0.00002m 22. 0.00001m 23. 0.000005m 24. 0.000002m 25. 0.000001m	1. 100m 2. 50m 3. 20m 4. 10m 5. 5m 6. 2m 7. 1m 8. 0.5m 9. 0.2m 10. 0.1m 11. 0.05m 12. 0.02m 13. 0.01m 14. 0.005m 15. 0.002m 16. 0.001m 17. 0.0005m 18. 0.0002m 19. 0.0001m 20. 0.00005m 21. 0.00002m 22. 0.00001m 23. 0.000005m 24. 0.000002m 25. 0.000001m	1. 100m 2. 50m 3. 20m 4. 10m 5. 5m 6. 2m 7. 1m 8. 0.5m 9. 0.2m 10. 0.1m 11. 0.05m 12. 0.02m 13. 0.01m 14. 0.005m 15. 0.002m 16. 0.001m 17. 0.0005m 18. 0.0002m 19. 0.0001m 20. 0.00005m 21. 0.00002m 22. 0.00001m 23. 0.000005m 24. 0.000002m 25. 0.000001m	1. 100m 2. 50m 3. 20m 4. 10m 5. 5m 6. 2m 7. 1m 8. 0.5m 9. 0.2m 10. 0.1m 11. 0.05m 12. 0.02m 13. 0.01m 14. 0.005m 15. 0.002m 16. 0.001m 17. 0.0005m 18. 0.0002m 19. 0.0001m 20. 0.00005m 21. 0.00002m 22. 0.00001m 23. 0.000005m 24. 0.000002m 25. 0.000001m



WARNING NOTES

1. The site is located within the Portside Wharf area, which is a designated area for development. The site is bounded by Hercules Street to the left and Portside Wharf to the right.

2. The site is located within the Portside Wharf area, which is a designated area for development. The site is bounded by Hercules Street to the left and Portside Wharf to the right.

3. The site is located within the Portside Wharf area, which is a designated area for development. The site is bounded by Hercules Street to the left and Portside Wharf to the right.

4. The site is located within the Portside Wharf area, which is a designated area for development. The site is bounded by Hercules Street to the left and Portside Wharf to the right.

5. The site is located within the Portside Wharf area, which is a designated area for development. The site is bounded by Hercules Street to the left and Portside Wharf to the right.

PROPOSED BUILDING

603(P1)

904

901

596

804

SP 172040

SP 172010

SP 172015

SP 172020

SP 172025

SP 172030

SP 172035

SP 172040

SP 172045

SP 172050

SP 172055

SP 172060

SP 172065

SP 172070

SP 172075

SP 172080

SP 172085

SP 172090

SP 172095

SP 172100

SP 172105

SP 172110

SP 172115

SP 172120

SP 172125

SP 172130

SP 172135

SP 172140

SP 172145

SP 172150

SP 172155

SP 172160

SP 172165

SP 172170

SP 172175

SP 172180

SP 172185

SP 172190

SP 172195

SP 172200

SP 172205

SP 172210

SP 172215

SP 172220

SP 172225

SP 172230

SP 172235

SP 172240

SP 172245

SP 172250

SP 172255

SP 172260

SP 172265

SP 172270

SP 172275

SP 172280

SP 172285

SP 172290

SP 172295

SP 172300

SP 172305

SP 172310

SP 172315

SP 172320

SP 172325

SP 172330

SP 172335

SP 172340

SP 172345

SP 172350

SP 172355

SP 172360

SP 172365

SP 172370

SP 172375

SP 172380

SP 172385

SP 172390

SP 172395

SP 172400

SP 172405

SP 172410

SP 172415

SP 172420

SP 172425

SP 172430

SP 172435

SP 172440

SP 172445

SP 172450

SP 172455

SP 172460

SP 172465

SP 172470

SP 172475

SP 172480

SP 172485

SP 172490

SP 172495

SP 172500

SP 172505

SP 172510

SP 172515

SP 172520

SP 172525

SP 172530

SP 172535

SP 172540

SP 172545

SP 172550

SP 172555

SP 172560

SP 172565

SP 172570

SP 172575

SP 172580

SP 172585

SP 172590

SP 172595

SP 172600

SP 172605

SP 172610

SP 172615

SP 172620

SP 172625

SP 172630

SP 172635

SP 172640

SP 172645

SP 172650

SP 172655

SP 172660

SP 172665

SP 172670

SP 172675

SP 172680

SP 172685

SP 172690

SP 172695

SP 172700

SP 172705

SP 172710

SP 172715

SP 172720

SP 172725

SP 172730

SP 172735

SP 172740

SP 172745

SP 172750

SP 172755

SP 172760

SP 172765

SP 172770

SP 172775

SP 172780

SP 172785

SP 172790

SP 172795

SP 172800

SP 172805

SP 172810

SP 172815

SP 172820

SP 172825

SP 172830

SP 172835

SP 172840

SP 172845

SP 172850

SP 172855

SP 172860

SP 172865

SP 172870

SP 172875

SP 172880

SP 172885

SP 172890

SP 172895

SP 172900

SP 172905

SP 172910

SP 172915

SP 172920

SP 172925

SP 172930

SP 172935

SP 172940

SP 172945

SP 172950

SP 172955

SP 172960

SP 172965

SP 172970

SP 172975

SP 172980

SP 172985

SP 172990

SP 172995

SP 173000

SP 173005

SP 173010

SP 173015

SP 173020

SP 173025

SP 173030

SP 173035

SP 173040

SP 173045

SP 173050

SP 173055

SP 173060

SP 173065

SP 173070

SP 173075

SP 173080

SP 173085

SP 173090

SP 173095

SP 173100

SP 173105

SP 173110

SP 173115

SP 173120

SP 173125

SP 173130

SP 173135

SP 173140

SP 173145

SP 173150

SP 173155

SP 173160

SP 173165

SP 173170

SP 173175

SP 173180

SP 173185

SP 173190

SP 173195

SP 173200

SP 173205

SP 173210

SP 173215

SP 173220

SP 173225

SP 173230

SP 173235

SP 173240

SP 173245

SP 173250

SP 173255

SP 173260

SP 173265

SP 173270

SP 173275

SP 173280

SP 173285

SP 173290

SP 173295

SP 173300

SP 173305

SP 173310

SP 173315

SP 173320

SP 173325

SP 173330

SP 173335

SP 173340

SP 173345

SP 173350

SP 173355

SP 173360

SP 173365

SP 173370

SP 173375

SP 173380

SP 173385

SP 173390

SP 173395

SP 173400

SP 173405

SP 173410

SP 173415

SP 173420

SP 173425

SP 173430

SP 173435

SP 173440

SP 173445

SP 173450

SP 173455

SP 173460

SP 173465

SP 173470

SP 173475

SP 173480

SP 173485

SP 173490

SP 173495

SP 173500

SP 173505

SP 173510

SP 173515

SP 173520

SP 173525

SP 173530

SP 173535

SP 173540

SP 173545

SP 173550

SP 173555

SP 173560

SP 173565

SP 173570

SP 173575

SP 173580

SP 173585

SP 173590

SP 173595

SP 173600

SP 173605

SP 173610

SP 173615

SP 173620

SP 173625

SP 173630

SP 173635

SP 173640

SP 173645

SP 173650

SP 173655

SP 173660

SP 173665

SP 173670

SP 173675

SP 173680

SP 173685

SP 173690

SP 173695

SP 173700

SP 173705

SP 173710

SP 173715

SP 173720

SP 173725

SP 173730

SP 173735

SP 173740

SP 173745

SP 173750

SP 173755

SP 173760

SP 173765

SP 173770

SP 173775

SP 173780

SP 173785

SP 173790

SP 173795

SP 173800

SP 173805

SP 173810

SP 173815

SP 173820

SP 173825

SP 173830

SP 173835

SP 173840

SP 173845

SP 173850

SP 173855

SP 173860

SP 173865

SP 173870

SP 173875

SP 173880

SP 173885

SP 173890

SP 173895

SP 173900

SP 173905

SP 173910

SP 173915

SP 173920

SP 173925

SP 173930

SP 173935

SP 173940

SP 173945

SP 173950

SP 173955

SP 173960

SP 173965

SP 173970

SP 173975

SP 173980

SP 173985

SP 173990

SP 173995

SP 174000

SP 174005

SP 174010

SP 174015

SP 174020

SP 174025

SP 174030

SP 174035

SP 174040

SP 174045

SP 174050

SP 174055

SP 174060

SP 174065

SP 174070

SP 174075

SP 174080

SP 174085

SP 174090

SP 174095

SP 174100

SP 174105

SP 174110

SP 174115

SP 174120

SP 174125

SP 174130

SP 174135

SP 174140

SP 174145

SP 174150

SP 174155

SP 174160

SP 174165

SP 174170

SP 174175

SP 174180

SP 174185

SP 174190

SP 174195

SP 174200

SP 174205

SP 174210

SP 174215

SP 174220

SP 174225

SP 174230

SP 174235

SP 174240

SP 174245

SP 174250

SP 174255

SP 174260

SP 174265

SP 174270

SP 174275

SP 174280

SP 174285

SP 174290

SP 174295

SP 174300

SP 174305

SP 174310

SP 174315

SP 174320

SP 174325

SP 174330

SP 174335

SP 174340

SP 174345

SP 174350

SP 174355

SP 174360

SP 174365

SP 174370

SP 174375

SP 174380

SP 174385

SP 174390

SP 174395

SP 174400

SP 174405

SP 174410

SP 174415

SP 174420

SP 174425

SP 174430

SP 174435

SP 174440

SP 174445

SP 174450

SP 174455

SP 174460

SP 174465

SP 174470

SP 174475

SP 174480

SP 174485

SP 174490

SP 174495

SP 174500

SP 174505

SP 174510

SP 174515

SP 174520

SP 174525

SP 174530

SP 174535

SP 174540

SP 174545

SP 174550

SP 174555

SP 174560

SP 174565

SP 174570

SP 174575

SP 174580

SP 174585

SP 174590

SP 174595

SP 174600

SP 174605

SP 174610

SP 174615

SP 174620

SP 174625

SP 174630

SP 174635

SP 174640

SP 174645

SP 174650

SP 174655

SP 174660

SP 174665

SP 174670

SP 174675

SP 174680

SP 174685

SP 174690

SP 174695

SP 174700

SP 174705

SP 174710

SP 174715

SP 174720

SP 174725

SP 174730

SP 174735

SP 174740

SP 174745

SP 174750

SP 174755

SP 174760

SP 174765

SP 174770

SP 174775

SP 174780

SP 174785

SP 174790

SP 174795

SP 174800

SP 174805

SP 174810

SP 174815

SP 174820

SP 174825

SP 174830

SP 174835

SP 174840

SP 174845

SP 174850

SP 174855

SP 174860

SP 174865

SP 174870

SP 174875

SP 174880

SP 174885

SP 174890

SP 174895

SP 174900

SP 174905

SP 174910

SP 174915

SP 174920

SP 174925

SP 174930

SP 174935

SP 174940

SP 174945

SP 174950

SP 174955

SP 174960

SP 174965

SP 174970

SP 174975

SP 174980

SP 174985

SP 174990

SP 174995

SP 175000